


3-wire Serial EEPROMs 1k/2k/4k

FEATURES

- Internally organized as 128×8 or 64×16(1k) 256×8 or 128×16(2K), 512×8 or 256×16(4K)
- Wide-voltage range operation 1.8V-5.5V
- 3-wire serial interface bus
- Data retention:100years
- High endurance 1,000,000 Write Cycles
- 2 MHz(5V)clock rate
- Sequential read operation
- Self-timed write cycle(10ms max)
- 8-pin DIP,8-pin JEDEC SOP,and 8-pin MSOP Packages




ORDERING INFORMATION:

DEVICE	Package Type	MARKING	Packing	Packing Qty
AT93C46N	DIP-8	93C46	TUBE	2000box/reel
AT93C56N	DIP-8	93C56	TUBE	2000box/reel
AT93C66N	DIP-8	93C66	REEL	2000box/reel
AT93C46M/TR	SOP-8	93C46	REEL	2500pcs/reel
AT93C56M/TR	SOP-8	93C56	REEL	2500pcs/reel
AT93C66M/TR	SOP-8	93C66	REEL	2500pcs/reel
AT93C46MM/TR	MSOP-8	93C46	REEL	3000pcs/reel
AT93C56MM/TR	MSOP-8	93C56	REEL	3000pcs/reel
AT93C66MM/TR	MSOP-8	93C66	REEL	3000pcs/reel

DESCRIPTION

The AT93Cxx family provides 1k,2k and 4k of serial electrically erasable and programmable read-only memory(EEPROM).The wide Vdd range allows for low-voltage operation down to 1.8V and up to 5.5V The device,fabricated using traditional CMOS EEPROM technology,is optimized for many industrial and commercial applications where low-voltage and low-power operation is essential.The AT93C46/56/66 is available in 8-pin DIP,8-pin JEDEC SOP,and 8-pin MSOP packages and is accessed via a 3-wire serial interface.

Figure 1. Pin Configuration



Pin Name	Function
CS	Chip Select
SK	Serial Data Clock
DI	Serial Data Input
DO	Serial Data Output
GND	Ground
Vcc	Power Supply
ORG	Internal Organization
NC	No Connect


ABSOLUTE MAXIMUM RATINGS

Condition	Min	Max
Operating Temperature	-40°C	+85°C
Storage Temperature	-65°C	+150°C
Voltage on Any Pin with		
Respect to Ground	-1.0V	VCC+ 7.0V
Maximum Operating Voltage	-	6.25V
DC Output Current	-	5.0 mA
Lead Temperature (Soldering, 10 seconds)	-	260°C

Note: Stresses beyond those listed under “Absolute Maximum Ratings” may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of this specification is not implied.

Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

Figure 2. Block Diagram



Notes

The ORG pin is used to select between x8 and x16 mode.

When the pin is connected to Vcc, x16 mode is selected. Otherwise, the ORG pin should be grounded in order to select x8 mode.

The interface for the AT93C46 / 56 / 66 is accessed through four different signals:

Chip Select (CS), Data Input (DI), Data Output (DO), and Serial Data Clock (SK). The Chip Select (CS) signal must be pulled high before issuing a command through the Data Input (DI) pin. The Serial Data Clock (SK) signal is used in conjunction with the Data Input (DI) pin.

PIN CAPACITANCE

Applicable over recommended operating range from $T_A = 25^{\circ}\text{C}$, $f = 1.0\text{ MHz}$, $V_{CC} = +5.0\text{V}$

Symbol	Test Condition	Max	Units	Condition
C_{OUT}	Output Capacitance (DO)	5	pF	$V_{OUT} = 0\text{V}$
C_{IN}	Input Capacitance (CK, SK, DI)	5	pF	$V_{IN} = 0\text{V}$

DC CHARACTERISTICS

Applicable over recommended operating range from:

$T_{AMB} = -40^{\circ}\text{C}$ to $+85^{\circ}\text{C}$, $V_{CC} = +1.8\text{V}$ to $+5.5\text{V}$ (unless otherwise noted)

Symbol	Parameter	Test Condition	Min	Typ	Max	Units
V_{CC1}	Supply Voltage		1.8		5.5	V
V_{CC2}	Supply Voltage		2.7		5.5	V
V_{CC3}	Supply Voltage		4.5		5.5	V
I_{CC}	Supply Current $V_{CC}=5.0\text{V}$	READ at 1 MHz		0.5	2.0	mA
I_{CC}	Supply Current $V_{CC}=5.0\text{V}$	WRITE at 1 MHz		0.5	2.0	mA
I_{SB1}	Standby Current $V_{CC}=1.8\text{V}$	CS=0V		0	0.1	μA
I_{SB2}	Standby Current $V_{CC}=2.7\text{V}$	CS=0V		6.0	10.0	μA
I_{SB3}	Standby Current $V_{CC}=5.0\text{V}$	CS=0V		17	3.0	μA
I_{LI}	Input Leakage Current	$V_{IN}=0\text{V}$ to V_{CC}		0.1	3.0	μA
I_{LO}	Output Leakage Current	$V_{IN}=0\text{V}$ to V_{CC}		0.1	3.0	μA
$V_{IL1}^{(1)}$ $V_{IH1}^{(1)}$	Input Low Level Input High Level	$2.7\text{V} < V_{CC} < 5.5\text{V}$	-0.6 2.0		0.8 $V_{CC}+1$	V
$V_{IL2}^{(1)}$ $V_{IH2}^{(1)}$	Input Low Level Input High Level	$1.8\text{V} < V_{CC} < 2.7\text{V}$	-0.6 $V_{CC} \times 0.7$		$V_{CC} \times 0.3$ $V_{CC}+1$	V
V_{OL1} V_{OH1}	Output Low Level Output High Level	$2.7\text{V} < V_{CC} < 5.5\text{V}$; $I_{OL}=2.1\text{mA}$ $I_{OH}=-0.4\text{mA}$	2.4		0.4	V
V_{OL2} V_{OH2}	Output Low Level Output High LevelR	$1.8\text{V} < V_{CC} < 0.7\text{V}$; $I_{OL}=0.15\text{mA}$ $I_{OH}=-100\mu\text{A}$	$V_{CC}-0.2$		0.2	V

Note: 1. V_{IL} and V_{IH} max are reference only and are not tested

AC CHARACTERISTICS

Applicable over recommended operating range from:

TAMB=-40°C to +85°C, Vcc= As specified, CL=1 TTL Gate&100pF (unless otherwise noted).

Symbol	Parameter	Test Condition		Min	Typ	Max	Units
f _{SK}	Clock Frequency, SK	4.5V < V _{CC} < 5.5V 2.7V < V _{CC} < 5.5V 1.8V < V _{CC} < 5.5V		0 0 0		2 1 0.25	MHz
t _{SKH}	SK High Time	4.5V < V _{CC} < 5.5V 2.7V < V _{CC} < 5.5V 1.8V < V _{CC} < 5.5V		250 250 1000			ns
t _{SKL}	SK Low Time	4.5V < V _{CC} < 5.5V 2.7V < V _{CC} < 5.5V 1.8V < V _{CC} < 5.5V		250 250 1000			ns
t _{CS}	Minimum CS Low Time	4.5V < V _{CC} < 5.5V 2.7V < V _{CC} < 5.5V 1.8V < V _{CC} < 5.5V		250 250 1000			ns
t _{CSS}	CS Setup Time	Relative to SK	4.5V < V _{CC} < 5.5V 2.7V < V _{CC} < 5.5V 1.8V < V _{CC} < 5.5V	50 50 200			ns
t _{DIS}	DI Setup Time	Relative to SK	4.5V < V _{CC} < 5.5V 2.7V < V _{CC} < 5.5V 1.8V < V _{CC} < 5.5V	100 100 400			ns
t _{CSH}	CS Hold Time	Relative to SK		0			ns
t _{DIH}	DI Hold Time	Relative to SK	4.5V < V _{CC} < 5.5V 2.7V < V _{CC} < 5.5V 1.8V < V _{CC} < 5.5V	100 100 400			ns
t _{PD1}	Output Delay to "1"	AC Test	4.5V < V _{CC} < 5.5V 2.7V < V _{CC} < 5.5V 1.8V < V _{CC} < 5.5V			250 250 1000	ns
t _{PD0}	Output Delay to "0"	AC Test	4.5V < V _{CC} < 5.5V 2.7V < V _{CC} < 5.5V 1.8V < V _{CC} < 5.5V			250 250 1000	ns
t _{SV}	CS to Status Valid	AC Test	4.5V < V _{CC} < 5.5V 2.7V < V _{CC} < 5.5V 1.8V < V _{CC} < 5.5V			250 250 1000	ns
t _{DF}	CS to DO in High Impedance	AC Test CS = V _{IL}	4.5V < V _{CC} < 5.5V 2.7V < V _{CC} < 5.5V 1.8V < V _{CC} < 5.5V			100 100 400	ns
t _{WP}	Write Cycle Time		4.5V < V _{CC} < 5.5V		3	10	ms
Endurance	5.0V, 25°C			1M			Write Cycles

INSTRUCTION SET FOR THE AT93C46

Instruction	SB	Op Code	Address		Data		Comments
			X8	X16	X8	X16	
READ	1	10	A ₆ – A ₀	A ₅ – A ₀			Reads data stored at specified memory location.
EWEN	1	00	11xxxxx	11xxxx			Write enable command (must be issued before any erase or write operation).
ERASE	1	11	A ₆ – A ₀	A ₅ – A ₀			Erases memory location A _n – A ₀

WRITE	1	01	$A_6 - A_0$	$A_5 - A_0$	$D_7 - D_0$	$D_{15} - D_0$	Writes to memory location $A_n - A_0$
ERAL	1	00	10xxxxx	10xxxx			Erases all memory locations. Valid only at $V_{cc} = 4.5V$ to $5.5V$
WRAL 1		00	01xxxxx	01xxxx	$D_7 - D_0$	$D_{15} - D_0$	Writes all memory locations. Valid only at $V_{cc} = 4.5V$ to $5.5V$
EWDS	1	00	00xxxxx	00xxxx			Disables all erase or write instructions

Note: The X's in the address field represent don't care values and must be clocked.

INSTRUCTION SET FOR THE AT93C46/56/66

Instruction	SB	Op Code	Address		Data		Comments
			X8	X16	X8	X16	
READ	1	10	$A_8 - A_0$	$A_7 - A_0$			Reads data stored at specified memory location.
EWEN	1	00	11xxxxxxx	11xxxxxxx			Write enable command (must be issued before any erase or write operation).
ERASE	1	11	$A_8 - A_0$	$A_7 - A_0$			Erase memory location $A_n - A_0$
WRITE	1	01	$A_8 - A_0$	$A_7 - A_0$	$D_7 - D_0$	$D_{15} - D_0$	Writes memory location $A_n - A_0$
ERAL	1	00	10xxxxxxx	10xxxxxxx			Erases all memory locations. Valid only at $V_{cc} = 4.5V$ to $5.5V$
WRAL 1		00	01xxxxxxx	01xxxxxxx	$D_7 - D_0$	$D_{15} - D_0$	Writes all memory locations. Valid only at $V_{cc} = 4.5V$ to $5.5V$.
EWDS	1	00	00xxxxxxx	00xxxxxxx			Disables all erase or write instructions

Note: The X's in the address field represent don't care values and must be clocked.

FUNCTIONAL DESCRIPTION

The AT93C46/56/66 supports 7 different instructions, which must be clocked serially using the CS, SK and DI pins. Before sending each of these instructions, the CS pin must first be pulled high followed by a START bit (logic '1'). The next sequence includes a 2-bit Op Code and usually an 8 or 16-bit address. The next description describes the various functions in the chip.

READ (READ): The Read (READ) instruction includes the Op Code ("10") followed by the memory address location to be read. After the instruction and address is sent, the data from the memory location can be clocked out using the serial output pin DO. The data changes on the rising edge of the clock, so the falling edge can be used to strobe the output.

Note that during shifting the last address bit, the DO pin is a dummy bit (logic "0").

ERASE/WRITE (EWEN): When the chip is first powered-on, no erase or write instructions can be issued. Only when the Erase/Write Enable (EWEN) instruction is sent will the system be allowed to write to the chip. The EWEN command only needs to be issued once

after being powered-on. To disable the chip again, the Erase/Write Disable (EWDS) command can be used.

ERASE (ERASE): The Erase (ERASE) instruction clears the designated memory location to a logical '1' state. After the Op Code and address location is inputted, the chip will enter into an erase cycle. When the cycle completes, the chip will automatically enter into standby mode.

WRITE (WRITE): The Write (WRITE) instruction is used to write to a specific memory location. If word mode (x16) is selected, then 16 bits of data will be written into the location. If byte mode (x8) is chosen, then 8 bits of data will be written into the location. The write cycle will begin automatically after the 8 or 16 bits are shifted into the chip.

ERASE ALL (ERAL): The Erase All (ERAL) instruction is primarily used for testing purposes and only functions when $V_{cc}=4.5\text{ V}$ to 5.5 V . This instruction will clear the entire memory array to '1'.

WRITE ALL (WRAL): The Write All (WRAL) instruction will program the entire memory array according to the 8 or 16-bit data pattern provided. The instruction will only be valid when $V_{cc}=4.5\text{ V}$ to 5.5 V .

ERASE/WRITE DISABLE (EWDS): The Erase/Write Disable (EWDS) instruction blocks any kind of erase or program operations from modifying the contents of the memory array. This instruction should be executed after erasing or programming to prevent accidental data loss.

Note also that the READ instruction will operate regardless of whether the chip is disabled from program and write operations.

READY/BUSY


To determine whether the chip has completed an erase or write operation, the CS signal can be pulled LOW for a minimum of 250 ns (t_{cs}) and then pulled back HIGH to enter Ready/Busy mode.

If the chip is currently in the programming cycle, t_{WP} , then the DO pin will go low (logical "0").

When the write cycle completes, the DO pin is pulled high (logical "1") to indicate that the part can receive another instruction. Note that the Ready/Busy polling cannot be done if the chip has already finished and returned back to standby mode.

TIMING DIAGRAMS

SYNCHRONOUS DATA TIMING



Note (1): This is the minimum SK period.


Organization Key for Timing Diagrams

I/O	93 C46(1K)		93 C56(2K)		93 C66(4K)	
	X8	X16	X8	X16	X8	X16
A_N	A_8	A_5	$A_8^{(1)}$	$A_7^{(2)}$	A_8	A_7
D_N	D_7	D_{15}	D_7	D_{15}	D_7	D_{15}


Notes:

- A_8 is a DON'T CARE value, but the extra clock is required.
- A_7 is a DON'T CARE value, but the extra clock is required.


READ TIMING




EWEN TIMING




EWDS TIMING



WRITE TIMING




WRITE TIMING




(1) Valid only at $V_{CC} = 4.5V$ to $5.5V$

ERASE TIMING




ERASE TIMING(1)



(1) Valid only at Vcc = 4.5V to 5.5V


PHYSICAL DIMENSIONS

DIP-8




Dimensions In Millimeters(DIP-8)											
Symbol:	A	B	D	D1	E	L	L1	a	b	c	d
Min:	6.10	9.00	8.10	7.42	3.10	0.50	3.00	1.50	0.85	0.40	2.54 BSC
Max:	6.68	9.50	10.9	7.82	3.55	0.70	3.60	1.55	0.90	0.50	

SOP-8



Dimensions In Millimeters(SOP-8)									
Symbol:	A	A1	B	C	C1	D	Q	a	b
Min:	1.35	0.05	4.90	5.80	3.80	0.40	0°	0.35	1.27 BSC
Max:	1.55	0.20	5.10	6.20	4.00	0.80	8°	0.45	

MSOP-8



Dimensions In Millimeters(MSOP-8)									
Symbol:	A	A1	B	C	C1	D	Q	a	b
Min:	0.80	0.05	2.90	4.75	2.90	0.35	0°	0.25	0.65 BSC
Max:	0.90	0.20	3.10	5.05	3.10	0.75	8°	0.35	

REVISION HISTORY

REVISION NUMBER	DATE	REVISION	PAGE
V1.0	2020-3	New	1-15
V1.1	2023-8	Update encapsulation type、Updated DIP-8 dimension	1、 12
V1.2	2024-11	Update Lead Temperature	3
V1.3	2025-11	Update important statements、 Update SOP-8 Dimension drawing	12、 15

IMPORTANT STATEMENT:

Huaguan Semiconductor reserves the right to change products and services offered without prior notice. Customers should obtain the latest relevant information before placing orders and verify that such information is current and complete. Huaguan Semiconductor assumes no responsibility or liability for altered documents.

Customers are responsible for complying with safety standards and implementing safety measures when using Huaguan Semiconductor products in system design and end-product manufacturing. You assume full responsibility for: selecting the appropriate Huaguan Semiconductor products for your application; designing, validating, and testing your application; and ensuring that your application complies with applicable standards and all other safety, security, or other requirements. This is to prevent potential risks that may lead to personal injury or property damage.

Huaguan Semiconductor products are not approved for use in life support, military, aerospace, or other high-risk applications. Huaguan products are neither intended nor warranted for use in such systems or equipment. Any failure or malfunction may lead to personal injury or severe property damage. Such applications are deemed "Unsafe Use." Unsafe Use includes, but is not limited to: surgical and medical equipment, nuclear energy control equipment, aircraft or spacecraft instruments, control or operation of vehicle power, braking, or safety systems, traffic signal instruments, all types of safety devices, and any other applications intended to support or sustain life. Huaguan Semiconductor shall not be liable for consequences resulting from Unsafe Use in these fields. Users must independently evaluate and assume all risks. Any issues, liabilities, or losses arising from the use of products beyond their approved applications shall be solely borne by the user. Users may not claim any compensation from Huaguan Semiconductor based on these terms. If any third party claims against Huaguan Semiconductor due to such Unsafe Use, the user shall compensate Huaguan Semiconductor for all resulting damages and liabilities.

Huaguan Semiconductor provides technical and reliability data (including datasheets), design resources (including reference designs), application or other design advice, web tools, safety information, and other resources for its semiconductor products. However, no guarantee is made that these resources are free from defects, and no express or implied warranties are provided. The use of testing and other quality control techniques is limited to Huaguan Semiconductor's quality assurance scope. Not all parameters of each device are tested.

Huaguan Semiconductor's documentation authorizes you to use these resources only for developing applications related to the products described herein. You are not granted rights to any other intellectual property of Huaguan Semiconductor or any third party. Any other reproduction or display of these resources is strictly prohibited. You shall fully indemnify Huaguan Semiconductor and its agents against any claims, damages, costs, losses, and liabilities arising from your use of these resources. Huaguan Semiconductor shall not be held responsible.