

1.Features

- $V_{DS(V)}=40V$
- $I_D=195A$
- $R_{DS(ON)}<2m\Omega(V_{GS}=10V)$



2.Applications

- OR-ing and redundant power switches
- DC/DC and AC/DC converters
- DC/AC Inverters

3.Pinning information

Pin	Symbol	Description
1	G	GATE
2	D	DRAIN
3	S	SOURCE

TO-220



4.Absolute Maximum Ratings

Parameter		Symbol	Rating	Units
Continuous Drain Current, $V_{GS}=10V$ (Silicon Limited)	$T_C=25^{\circ}C$	I_D	250 ①	A
Continuous Drain Current, $V_{GS}=10V$ (Silicon Limited)	$T_C=100^{\circ}C$		180	A
Continuous Drain Current, $V_{GS}=10V$ (Wire Bond Limited)	$T_C=25^{\circ}C$		195	A
Pulsed Drain Current ②		I_{DM}	1000	A
Maximum Power Dissipation	$T_C=25^{\circ}C$	P_D	230	W
Linear Derating Factor			1.5	W/ $^{\circ}C$
Gate-to-Source Voltage		V_{GS}	± 20	V
Storage Temperature Range		T_J, T_{STG}	-55 to 175	$^{\circ}C$
Soldering Temperature, for 10 seconds (1.6mm from case)			300	$^{\circ}C$
Mounting torque, 6-32 or M3 screw			10lbin (1.1Nm)	$^{\circ}C$



Single Pulse Avalanche Energy ③	$E_{AS(Thermally\ limited)}$	350	mJ
Single Pulse Avalanche Energy ⑨	$E_{AS(Thermally\ limited)}$	802	mJ
Avalanche Current ②	I_{AR}	See Fig. 13, 14	A
Repetitive Avalanche Energy ②	E_{AR}		22a, 22b mJ

5. Thermal resistance rating

Parameter	Symbol	Typ	Max	Units
Junction-to-Case ⑧	$R_{\theta JC}$		0.65	°C/W
Case-to-Sink, Flat Greased Surface	$R_{\theta CS}$	0.5		°C/W
Junction-to-Ambient ⑧	$R_{\theta JA}$		62	°C/W



6. Electrical Characteristics @ $T_J = 25^\circ\text{C}$ (unless otherwise specified)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Drain-to-Source Breakdown Voltage	$V_{(BR)DSS}$	$I_D=250\mu\text{A}$, $V_{GS}=0\text{V}$	40			V
Breakdown Voltage Temp. Coefficient	$\Delta V_{(BR)DSS}/\Delta T_J$	$I_D=1\text{mA}$, Reference to 25°C ②		0.029		V/ $^\circ\text{C}$
Static Drain-to-Source On-Resistance	$R_{DS(ON)}$	$V_{GS}=10\text{V}$, $I_D=100\text{A}$		1.5	2	m Ω
		$V_{GS}=6\text{V}$, $I_D=50\text{A}$		1.8		m Ω
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}$, $I_D=150\mu\text{A}$	2.2	3	3.9	V
Drain-to-Source Leakage Current	I_{DSS}	$V_{DS}=40\text{V}$, $V_{GS}=0\text{V}$			1	μA
		$V_{DS}=40\text{V}$, $V_{GS}=0\text{V}$, $T_J=125^\circ\text{C}$			150	μA
Gate-to-Source Forward Leakage	I_{GSS}	$V_{GS}=20\text{V}$			100	nA
Gate-to-Source Reverse Leakage		$V_{GS}=-20\text{V}$			-100	nA
Internal Gate Resistance	R_g			2.2		Ω
Forward Transconductance	g_{FS}	$V_{DS}=10\text{V}$, $I_D=100\text{A}$	160			S
Total Gate Charge	Q_g	$I_D=100\text{A}$, $V_{DS}=20\text{V}$ $V_{GS}=10\text{V}$ ⑤		150	225	nC
Gate-to-Source Charge	Q_{gs}			41		nC
Gate-to-Drain ("Miller") Charge	Q_{gd}			51		nC
Total Gate Charge Sync. (Q_g-Q_{gd})	Q_{sync}	$I_D=100\text{A}$, $V_{DS}=20\text{V}$, $V_{GS}=10\text{V}$		99		nC
Turn-On Delay Time	$t_{D(on)}$	$V_{DD}=20\text{V}$, $I_D=30\text{A}$ $R_G=2.7\Omega$, $V_{GS}=10\text{V}$ ⑤		19		ns
Rise Time	t_r			70		ns
Turn-Off Delay Time	$t_{D(off)}$			78		ns
Fall Time	t_f			53		ns
Input Capacitance	C_{iss}	$V_{GS}=0\text{V}$, $V_{DS}=25\text{V}$ $f=1\text{MHz}$, See Fig. 5		7330		pF
Output Capacitance	C_{oss}			1095		pF
Reverse Transfer Capacitance	C_{rss}			745		pF
Effective Output Capacitance (Energy Related) ⑦	$C_{oss\text{eff.}(ER)}$	$V_{GS}=0\text{V}$, $V_{DS}=0\text{V}$ to 32V ⑦ See Fig. 11		1310		pF
Effective Output Capacitance (Time Related) ⑥	$C_{oss\text{eff.}(TR)}$	$V_{GS}=0\text{V}$, $V_{DS}=0\text{V}$ to 32V ⑥		1735		pF



Diode Characteristics						
Continuous Source Current (Body Diode)	I_S	MOSFET symbol showing the integral reverse p-n junction diode.			250 ^①	A
Pulsed Source Current (Body Diode) ^②	I_{SM}				1000	A
Diode Forward Voltage	V_{SD}	$T_J=25^\circ\text{C}, I_S=100, V_{GS}=0\text{V}$ ^⑤		1	1.3	V
Peak Diode Recovery ^④	dv/dt	$T_J=175^\circ\text{C}, I_S=100, V_{GS}=40\text{V}$		3.1		V/ns
Reverse Recovery Time	t_{rr}	$T_J=25^\circ\text{C}, V_R=34\text{V}$		30		ns
		$T_J=125^\circ\text{C}, I_F=100\text{A}$		30		ns
Reverse Recovery Charge	Q_{rr}	$T_J=25^\circ\text{C}, di/dt=100\text{A}/\mu\text{s}$ ^⑤		24		nC
		$T_J=125^\circ\text{C}$		25		nC
Reverse Recovery Current	I_{RRM}	$T_J=25^\circ\text{C}$		1.3		A

Notes:

- ① Calculated continuous current based on maximum allowable junction temperature. Bond wire current limit is 195A. Note that current limitations arising from heating of the device leads may occur with some lead mounting arrangements.
- ② Repetitive rating; pulse width limited by max. junction temperature.
- ③ Limited by T_{Jmax} , starting $T_J=25^\circ\text{C}$, $L=0.069\text{mH}$, $R_G=50\Omega$, $I_{AS}=100\text{A}$, $V_{GS}=10\text{V}$.
- ④ $I_{SD} \leq 100\text{A}$, $di/dt \leq 1166\text{A}/\mu\text{s}$, $V_{DD} \leq V_{(BR)DSS}$, $T_J \leq 175^\circ\text{C}$.
- ⑤ Pulse width $\leq 400\mu\text{s}$; duty cycle $\leq 2\%$.
- ⑥ C_{oss} eff. (TR) is a fixed capacitance that gives the same charging time as C_{oss} while V_{DS} is rising from 0 to 80% V_{DSS} .
- ⑦ C_{oss} eff. (ER) is a fixed capacitance that gives the same energy as C_{oss} while V_{DS} is rising from 0 to 80% V_{DSS} .
- ⑧ R_θ is measured at T_J approximately 90°C .
- ⑨ Limited by T_{Jmax} , starting $T_J=25^\circ\text{C}$, $L=1\text{mH}$, $R_G=50\Omega$, $I_{AS}=40\text{A}$, $V_{GS}=10\text{V}$.



7.1 Typical Characteristics




Figure 1: Typical On-Resistance vs. Gate Voltage




Figure 2: Maximum Drain Current vs. Case Temperature




Figure 3: Typical Output Characteristics




Figure 4: Typical Output Characteristics




Figure 5: Typical Transfer Characteristics




Figure 6: Normalized On-Resistance vs. Temperature



7.2 Typical Characteristics




Figure 7: Typical Capacitance vs. Drain-to-Source Voltage




Figure 8: Typical Gate Charge vs. Gate-to-Source Voltage




Figure 9: Typical Source-Drain Diode Forward Voltage




Figure 10: Maximum Safe Operating Area




Figure 11: Drain-to-Source Breakdown Voltage




Figure 12: Typical C_{OSS} Stored Energy



7.3 Typical Characteristics




Figure 13: Maximum Effective Transient Thermal Impedance, Junction-to-Case




Figure 14: Typical Avalanche Current vs. Pulse width




Figure 15: Typical On-Resistance vs. Drain Current





Figure 16: Maximum Avalanche Energy vs. Temperature



7.4Typical Characterisitics





Notes on Repetitive Avalanche Curves , Figures 13, 14

1. Avalanche failures assumption: Purely a thermal phenomenon and failure occurs at a temperature far in excess of T_{jmax} .

This is validated for every part type.

2. Safe operation in Avalanche is allowed as long as T_{jmax} is not exceeded.

3. Equation below based on circuit and waveforms shown in Figures 16a, 16b.

4. $P_{D(ave)}$ = Average power dissipation per single avalanche pulse.

5. BV = Rated breakdown voltage (1.3 factor accounts for voltage increase during avalanche).

6. I_{av} = Allowable avalanche current.

7. ΔT = Allowable rise in junction temperature, not to exceed T_{jmax} (assumed as 25°C in Figure 13, 14).

t_{av} = Average time in avalanche.

D = Duty cycle in avalanche = $t_{av} \cdot f$

$Z_{thJC}(D, t_{av})$ = Transient thermal resistance


$P_{D(ave)} = 1/2 (1.3 \cdot BV \cdot I_{av}) = \Delta T / Z_{thJC}$

$I_{av} = 2\Delta T / [1.3 \cdot BV \cdot Z_{th}]$

$E_{AS(AR)} = P_{D(ave)} \cdot t_{av}$



8.1 TO-220 Package Outline Dimensions




DIMENSIONS (mm are the original dimensions)

Symbol	A	A1	A2	A3	B	B1	C	C1	D	E	F	G
Min	9.7	8.44	1.05	4.8	15.4	12.9	4.28	1.1	0.6	3.4	2.65	5.2
Max	10.3	8.84	1.25	5.2	16.2	13.5	4.68	1.5	1.0	3.8	3.25	5.8

Symbol	H	K	L	L1	M	N	P	Q	T	DIA
Min	0.4	2.9	12.8	2.7	1.15	2.49	2.1	8.7	W:0.35	⌀1.5
Max	0.6	3.3	13.6	3.3	1.35	2.59	2.7	9.3		(deep 0.2)



8.2 TO-220 Package Outline Dimensions




DIMENSIONS (mm are the original dimensions)

Symbol	A	B	C	C2	C3	D	E	G	H	L2	L3
Min	4.30	0.60	0.28	1.17	2.30	8.80	9.80	2.44	28.55	1.10	2.59
Max	4.70	1.00	0.48	1.37	2.70	9.20	10.20	2.64	29.15	1.50	2.89



9.Ordering information



yy: Year Code
ww: Week Code

Order Code	Package	Base QTY	Delivery Mode
UMW IRFB7437PBF	TO-220	1000	Tube and box



10.Disclaimer

UMW reserves the right to make changes to all products, specifications. Customers should obtain the latest version of product documentation and verify the completeness and currency of the information before placing an order.

When applying our products, please do not exceed the maximum rated values, as this may affect the reliability of the entire system. Under certain conditions, any semiconductor product may experience faults or failures. Buyers are responsible for adhering to safety standards and implementing safety measures during system design, prototyping, and manufacturing when using our products to prevent potential failure risks that could lead to personal injury or property damage.

Unless explicitly stated in writing, UMW products are not intended for use in medical, life-saving, or life-sustaining applications, nor for any other applications where product failure could result in personal injury or death. If customers use or sell the product for such applications without explicit authorization, they assume all associated risks.

When reselling, applying, or exporting, please comply with export control laws and regulations of China, the United States, the United Kingdom, the European Union, and other relevant countries, regions, and international organizations.

This document and any actions by UMW do not grant any intellectual property rights, whether express or implied, by estoppel or otherwise. The product names and marks mentioned herein may be trademarks of their respective owners.