

REVISION RECORD				
REV	ECN.	DESCRIPTION	DRFT	DATE

NOTE 1:

UL标准 (UL Standard)

1. 额定电压与电流: 300V/8A
Rated voltage/Rated current: 300V/8A
2. 功频耐压: AC1600V/Min
Withstanding Voltage: AC1600V/Min
3. 线径范围: 28~16AWG
Wire range: 28~16AWG

IEC标准 (IEC Standard)

1. 额定电压与电流: 250V/7A
Rated voltage/Rated current: 250V/7A
2. 线径范围: 0.5~1.5 mm²
Wire range : 0.5~1.5 mm²

NOTE 2:

1. 间距(Pitch): 3.50mm
2. 使用温度范围: -40℃~+105℃
Operating temperature: -40℃~+105℃
3. 剥线长度: 6~7mm
Stripping length: 6~7mm
4. 符合RoSH环保要求
RoHS Compliance
5. 额定扭矩: 1.8 [Lb. in]
(Rated torque): 1.8 [Lb. in]
6. 未标注公差表
Undimensioned tolerances

P 方向公差 (mm) Pitch range in mm			其他尺寸公差 (mm) Nominal dimension range in mm							
≤6	6 ~ 10	10 ~ 24	≤30	30 ~ 60	60 ~ 100	100 ~ 150	>150	0.1/		
±0.15	±0.20	±0.30	±0.20	±0.30	±0.50	±0.70	±1.00	±1*		

订购方式(HOW TO ORDER)

MX15EDGK-3.50-□□P-□ - □ - □□□□

型号	间距	极数
Series NO.	Pitch	Poles
1	1.27	2
2	1.27	4
3	1.27	6
4	1.27	8
5	1.27	10
6	1.27	12
7	1.27	14
8	1.27	16
9	1.27	18
10	1.27	20
11	1.27	22
12	1.27	24
13	1.27	26
14	1.27	28
15	1.27	30
16	1.27	32
17	1.27	34
18	1.27	36
19	1.27	38
20	1.27	40
21	1.27	42
22	1.27	44
23	1.27	46
24	1.27	48
25	1.27	50
26	1.27	52
27	1.27	54
28	1.27	56
29	1.27	58
30	1.27	60
31	1.27	62
32	1.27	64
33	1.27	66
34	1.27	68
35	1.27	70
36	1.27	72
37	1.27	74
38	1.27	76
39	1.27	78
40	1.27	80
41	1.27	82
42	1.27	84
43	1.27	86
44	1.27	88
45	1.27	90
46	1.27	92
47	1.27	94
48	1.27	96
49	1.27	98
50	1.27	100
51	1.27	102
52	1.27	104
53	1.27	106
54	1.27	108
55	1.27	110
56	1.27	112
57	1.27	114
58	1.27	116
59	1.27	118
60	1.27	120
61	1.27	122
62	1.27	124
63	1.27	126
64	1.27	128
65	1.27	130
66	1.27	132
67	1.27	134
68	1.27	136
69	1.27	138
70	1.27	140
71	1.27	142
72	1.27	144
73	1.27	146
74	1.27	148
75	1.27	150
76	1.27	152
77	1.27	154
78	1.27	156
79	1.27	158
80	1.27	160
81	1.27	162
82	1.27	164
83	1.27	166
84	1.27	168
85	1.27	170
86	1.27	172
87	1.27	174
88	1.27	176
89	1.27	178
90	1.27	180
91	1.27	182
92	1.27	184
93	1.27	186
94	1.27	188
95	1.27	190
96	1.27	192
97	1.27	194
98	1.27	196
99	1.27	198
100	1.27	200
101	1.27	202
102	1.27	204
103	1.27	206
104	1.27	208
105	1.27	210
106	1.27	212
107	1.27	214
108	1.27	216
109	1.27	218
110	1.27	220
111	1.27	222
112	1.27	224
113	1.27	226
114	1.27	228
115	1.27	230
116	1.27	232
117	1.27	234
118	1.27	236
119	1.27	238
120	1.27	

客户型号
Customer Request

颜色(Color)

1. 单间距
Single Pitch

2. 双间距
Double Pitch

1. 灰色 (Gray) 2. 蓝色 (Blue)
3. 黑色 (Black) 4. 绿色 (Green)
5. 橙色 (Orange) 6. 红色 (Red)
7. 黄色 (Yellow) 8. 白色 (White)
9. 透明 (Transparent)

N=No.of contacts

4	(Cage)方盒	(Copper alloy) 铜合金	(Ni plated)镀镍	PART NO.: /	 安徽亿思特电子科技有限公司 ANHUI EAST ELECTRONIC TECHNOLOGY CO., LTD.			
3	(Contact)触点	(Copper alloy) 铜合金	(Sn plated)镀锡	APPD: /				
2	(Screw)螺丝 M2.0	(Steel)钢	(Zn plated)镀锌	CHKD: /	型号	MX15EDGK-3.50-XXP-1X-XXAH		
1	(Housing)塑件	PA66	UL94V-0	DRFT: /				
ITEM	NAME OF PART	MATERIAL	NOTES	 THIED ANGLE PROJECTION	系列	MX15EDGK-3.50	页码	1/1
					图号	MX15EDGK350001	比例	1:1