



备注

- 1.Brass or purple copper,tin-plating
黄铜, 镀锡
- 2.Wire screw hole M3 (M4, M5, M6)
压线螺孔M3 (M4, M5, M6) 可定制
- 3.Current Rating: 40A
额定电流:40A
- 4.There shall be no defects such as
pin deformation and burrs.
不得有脚变形, 毛刺等缺陷
- 5.Unmarked dimensions refer to tolerances
未标注的尺寸参考公差
6. 扭矩: 0.79Nm

HC - * ** * * - ***** - * *** * - 07

Type	Thickness	Screw Thread	Welding Feet	Series	ISO/P	Product No.	Material
ISO/11 Teeth (特牙)	0.6mm, 0.8mm	4mm (螺牙)	25个	08010010080mm	ISO/11 S&T	产品号	碳钢, SUS304
ISO/vert Nut (特螺母)	1.0mm, 1.5mm	4mm (螺牙)	25个	ISO/100100mm	ISO/11 DIP		黄铜
ISO/vert Gasket (特垫片)	1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4.0mm	6mm (螺牙)	30个				黄铜/铜 (黄铜)



			GENERAL TOLERANCE	制 图 DRAWING	07					 深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO.,LTD		
			DIM	TOL	审 核 CHECK		产品名称 TITLE		PCB 焊接端子 厚度0.6 贴片 抽牙 M3 4焊脚 10.6x6.1x5.9mm		版 本 REV.	A
		5 or more	±0.35	批 准 APPROVAL		产品料号 PART NO.		HC-M0634-1006-D101-07		单 位 UNITS	mm	
1	初版发行		2~5	±0.25	比 例 SCALE		材料 MATERIAL		页 次 SHEET		1/1	
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE	0~2	±0.15	投 影 Projection							
			Angle	±3.0°								

