GBU3005 THRU GBU310

GBU Plastic-Encapsulate Bridge Rectifier

Reverse Voltage
50-1000 V

Forward Current
4.0 A max

Features

- Glass passivated chip
- Low reverse leakage current
- High surge current capability
- Reliable low cost construction utilizing molded plastic technique

Applications

- General purpose use in AC/DC bridge full wave rectification

Mechanical Data

- Case：GBU
- Polarity symbols being marked on body
- Molding compound meets UL 94V-0 flammability rating
- RoHS-compliant,Solder plated, solderable per MIL-STD-750,Method 2026

Appearance Image



Marking

- GBU3xx(005~10)

Maximum Ratings @ Ta = 25°C unless otherwise noted

PARAMETER	SYMBOL	UNIT	GBU3005	GBU301	GBU302	GBU304	GBU306	GBU308	GBU310
Repetitive peak reverse voltage	V_{RRM}	V	50	100	200	400	600	800	1000
Maximum RMS voltage	V_{RMS}	V	35	70	140	280	420	560	700
Maximum DC blocking Voltage	V_{DC}	V	50	100	200	400	600	800	1000
Maximum average output current@60Hz sine wave, resistance load	$I_{F(AV)}$	A	3.0						
Peak forward surge current 8.3 ms single half sine wave superimposed on rated load	I_{FSM}	A	80						
Peak forward surge current 1.0 ms single half sine wave superimposed on rated load		A	160						
Current squared time @1ms≤t<8.3ms Tj=25°C，Rating of per diode	I^2t	A^2S	26.56						
Storage temperature	T_{stg}	°C	-55～+150						
Junction temperature	T_j	°C	-55～+150						

Electrical Characteristics @ Ta = 25°C unless otherwise noted

PARAMETER	TEST CONDITIONS	SYMBOL	UNIT	GBU3005	GBU301	GBU302	GBU304	GBU306	GBU308	GBU310
Maximum instantaneous forward voltage	I_F=1.5A	V_F	V	1.0						
Maximum DC reverse currentat rated DC blocking voltage	V_R=V_{DC}, Tj=25°C	I_R	μA	5						
	V_R=V_{DC}, Tj=100°C	I_R		500						

Characteristic Curve (Typical)



FIG1.Derating Curve For Output Rectified Current



FIG2. Surge Forward Current Capability



FIG3.Typical Forward Characteristics



FIG4.Typical Reverse Characteristics

Marking and packet information



GBU****：Marking Model　　TOS：Brand Logo

Packaging information	
每盒	500PCS
每箱	5000PCS
脚长定制	支持

GBU Package outline dimensions



Dimensions in milimeters

Notice

XILONG reserves the right to make modifications,enhancements,improvements,corrections or other changes without further notice to any product herein.
xilong does not assume any liability arising out of the application or use of any product described herein.