



S-LESD3224CT1G

ESD Protection Diodes

1. FEATURES

- Low Leakage
- ESD protection
- Complies with IEC 61000-4-2 standards: Air discharge: $\pm 24\text{kV}$
Contact discharge: $\pm 24\text{kV}$
- We declare that the material of product compliance with RoHS requirements and Halogen Free.
- S-prefix for automotive and other applications requiring unique site and control change requirements; AEC-Q101 qualified and PPAP capable.



2. DEVICE MARKING AND ORDERING INFORMATION

Device	Marking	Shipping
S-LESD3224CT1G	PA	3000/Tape&Reel


3. MAXIMUM RATINGS($T_a = 25^\circ\text{C}$)

Parameter	Symbol	Limits	Unit
IEC 61000-4-2 (ESD) Contact		± 24	kV
Air		± 24	
peak pulse power@8/20 μs (Note 1)	PPP	160	W
peak pulse current @8/20 μs (Note 1)	IPP	4	A
Storage Temperature Range	Tstg	$-55 \sim +150$	$^\circ\text{C}$
Junction Temperature Range	TJ	$-55 \sim +150$	$^\circ\text{C}$

Note 1.Surge current waveform per Figure 1 according to IEC 61000-4-5.

4. ELECTRICAL CHARACTERISTICS (Ta= 25°C)

Symbol	Parameter
IPP	Maximum Reverse Peak Pulse Current
VC	Clamping Voltage @ IPP
VRWM	Working Peak Reverse Voltage
IR	Maximum Reverse Leakage Current @ VRWM
VBR	Breakdown Voltage @ IT
IT	Test Current
Ppk	Peak Power Dissipation
C	Capacitance @ VR = 0 and f = 1.0 MHz



5. ELECTRICAL CHARACTERISTICS (Ta= 25°C)

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Reverse stand-off voltage	VRWM				24	V
Breakdown Voltage	VBR	IT = 1mA	26		31	V
Reverse leakage current	IR	VR = 24V			0.1	μA
Clamping Voltage(Note 1)	VC	IPP = 1A, tp=8/20μs IPP = 4A, tp=8/20μs			35 45	V
Junction Capacitance	Cj	VR = 0V, f = 1MHz		10	15	pF

Note 1. Surge current waveform per Figure 1 according to IEC 61000-4-5.

6. ELECTRICAL CHARACTERISTICS CURVES




Figure 1. Pulse Waveform according to IEC 61000-4-5




Figure 2. Power Derating Curve




Figure 3. Clamping Voltage vs. Peak Pulse Current according to IEC 61000-4-5.






Figure 4. TLP Measurement

7.OUTLINE AND DIMENSIONS



SC70			
DIM	MIN	NOR	MAX
A	0.80	0.95	1.00
A1	0.00	0.05	0.10
A2	0.7 REF		
b	0.30	0.35	0.40
c	0.10	0.15	0.25
D	1.80	2.05	2.20
E	1.15	1.30	1.35
e	1.20	1.30	1.40
e1	0.65 BSC		
L	0.20	0.35	0.56
He	2.00	2.10	2.40
ALL Dimension in mm			

8.SOLDERING FOOTPRINT



SC70	
DIM	MIN
A	1.90
B	0.65
C	0.65
X	0.70
Y	0.90

DISCLAIMER

- Curve guarantee in the specification. The curve of test items with electric parameter is used as quality guarantee. The curve of test items without electric parameter is used as reference only.
- Before you use our Products for new Project, you are requested to carefully read this document and fully understand its contents. LRC shall not be in any way responsible or liable for failure, malfunction or accident arising from the use of any LRC's Products against warning, caution or note contained in this document.
- All information contained in this document is current as of the issuing date and subject to change without any prior notice. Before purchasing or using LRC's Products, please confirm the latest information with a LRC sales representative.

单击下面可查看定价，库存，交付和生命周期等信息

[>>LRC\(乐山无线电\)](#)