

Si8921 and Si8922 Isolated Amplifiers for Current Shunt Measurement

Applications

- Industrial, HEV, and renewable energy inverters
- AC, brushless, and dc motor controls and drives
- Variable speed motor control in consumer white goods
- Isolated switch mode and UPS power supplies
- Automotive onboard chargers, battery management systems, and charging stations

Features

- Low-voltage differential input: ± 62.5 mV and ± 250 mV options
- Low signal delay: 0.8 μ s
- Typical input offset: ± 0.40 μ V
- Typical gain error: $\pm 0.06\%$
- Excellent drift specifications
 - 0.5 μ V/ $^{\circ}$ C offset drift
 - -9 ppm/ $^{\circ}$ C typical gain drift
- Typical nonlinearity: 0.003% full-scale
- Typical SNR: 82 dB over 100 kHz bandwidth
- Typical THD: -88 dB
- High common-mode transient immunity: 75 kV/ μ s
- Automotive-grade OPNs available
 - AEC-Q100 qualification
 - AIAG-compliant PPAP documentation support
 - IMDS and CAMDS listing support
- Compact packages
 - 8-pin wide body stretched SOIC
 - 8-pin narrow body SOIC
- -40 to 125 $^{\circ}$ C
- For RoHS and other product compliance information, see the [Skyworks Certificate of Conformance](#).

Safety Regulatory Approvals

- UL recognized
 - 1577 (up to 5000 V_{RMS} for one minute)
- CSA certification conformity
 - 62368-1 (reinforced insulation)
 - 60601-1 (2 MOPP)

- VDE certification conformity
 - 60747-17 (reinforced insulation)
- CQC certification approval
 - GB4943.1 (reinforced insulation)

Description

The Si8921 and Si8922 galvanically isolated analog amplifiers feature low-voltage differential inputs, ideal for measuring voltage across a current shunt resistor or any place where a sensor must be isolated from the control system. The output is a differential analog signal amplified by either 8.2x or 32.8x.

The very low signal delays allow control systems to respond quickly to fault conditions or changes in load. Low offset and gain drift ensure that accuracy is maintained over the entire operating temperature range. Exceptionally high common-mode transient immunity means the Si8921/22 deliver accurate measurements, even in high-power switching environments found in motor drive systems and inverters.

The Si8921/22 isolated voltage-sensing amplifiers utilize Skyworks proprietary isolation technology, which supports up to 5.0 kV_{RMS} withstand voltage per UL1577. This technology enables high performance, reduced variation with temperature and age, tighter part-to-part matching, and longer lifetimes compared to other isolation technologies.

Automotive grade is available for certain part numbers. These products are built using automotive-specific flows at all steps in the manufacturing process to ensure the robustness and low defectivity required for automotive applications.

1. Functional Block Diagrams




Figure 1. Si8921 Functional Block Diagram




Figure 2. Si8922 Functional Block Diagram

2. Pin Descriptions

2.1. Si8921




Figure 3. Si8921 Pinout (Top View)

Table 1. Si8921 Pin Descriptions

Name	Pin Number	Description
VDDA	1	Input side power supply
AIP	2	Analog input high
AIN	3	Analog input low
GNDA	4	Input side ground
GNDB	5	Output side ground
AON	6	Analog output low
AOP	7	Analog output high
Vddb	8	Output side power supply

2.2. Si8922




Figure 4. Si8922 Pinout (Top View)

Table 2. Si8922 Pin Descriptions

Name	Pin Number	Description
VDDA	1	Input side power supply
AIP	2	Analog input high
AIN	3	Analog input low
GNDA	4	Input side ground
GNDB ¹	5	Output side ground
GNDB ¹	6	Output side ground
AO	7	Analog output
VDDB	8	Output side power supply

1. Both Pin 5 and Pin 6 must be connected to ground.

3. Functional Description

The input to the Si8921/22 is designed for low-voltage, differential signals. This is ideal for connection to low-resistance current shunt measurement resistors.

The Si8921A has a specified full-scale input range of $\pm 62.5\text{ mV}$, and the Si8921B has a specified full-scale input range of $\pm 250\text{ mV}$. In both cases, the internal gain is set so the full-scale output is 2.05 V . The Si8921 provides a differential output voltage while the Si8922 provides a single-ended output voltage.

The Si8921/22 modulates the analog signal in a unique way for transmission across the semiconductor-based isolation barrier. The input signal is first converted to a pulse-width modulated digital signal.

On the other side of the isolation barrier, the signal is demodulated. The resulting PWM signal is then used to faithfully reproduce the analog signal. This solution provides exceptional signal bandwidth and accuracy.

3.1. Fail-Safe and Low-Power Modes

The Si8921/22 implements a fail-safe output when the high-voltage-side supply voltage (VDDA) goes away. This is important for safe operation in systems with high safety requirements. The fail-safe output is nominally 2.8 V (Si8922) or -2.8 V (Si8921), which can be differentiated from the maximum clipping output voltage of 2.6 V to simplify diagnostics on the system level.

Table 3. Si8921 and Si8922 Output Voltages

Device	Output Voltage (VDDA Normal)	Output Voltage (VDDA Removed)
Si8921	$\sim \pm 2.6\text{ V}$	$\sim -2.8\text{ V}$
Si8922	$0\text{ to } \sim 2.6\text{ V}$	$\sim +2.8\text{ V}$

In addition to the fail-safe output, when a loss of VDDA supply occurs, the part automatically moves into a lower-power mode that reduces I_{DD}B current to approximately 1 mA . When the supply voltage is returned, normal operation begins in approximately $250\text{ }\mu\text{s}$.

3.2. Current Sense Application

In the driver circuit presented below, the Si8921 is used to amplify the voltage across the sense resistor, R_{SENSE} , and transmit the analog signal to the low-voltage domain across an isolation barrier. Isolation is needed because the voltage of R_{SENSE} with respect to ground swings between 0 V and the high voltage rail connected to the drain of Q1.

The load in this application can be a motor winding or a similar inductive winding. In a three-phase motor drive application, this circuit would be repeated three times, one for each phase. R_{SENSE} should be a small resistor value to reduce power loss. However, an excessively low resistance reduces the signal-to-noise ratio of the measurement. Si8921/22 offers two specified full-scale input options, ± 62.5 mV (Si8921A/22A) and ± 250 mV (Si8921B/22B), for optimizing the value of R_{SENSE} .




Figure 5. Current Sense Application

AIP and AIN connections to the R_{SENSE} resistor should be made as close as possible to each end of the R_{SENSE} resistor as trace resistance adds error to the measurement. The input to the Si8921/22 is differential, and the PCB traces back to the input pins should run in parallel. This ensures that any large noise transients that occur on the high-voltage side are coupled equally to the AIP and AIN pins and are rejected by the Si8921/22 as a common-mode signal.

The amplifier bandwidth of the Si8921/22 is approximately 600 kHz. If further input filtering is required, a passive differential RC low-pass filter can be placed between R_{SENSE} and the input pins.

As shown in [Figure 5](#), values of $R1 = R2 = 20\ \Omega$ and $C1 = 10\ \text{nF}$ provide a cutoff at approximately 400 kHz. For the lowest gain error, R1 and R2 should always be less than $33\ \Omega$ to keep the source impedance sufficiently low compared to the Si8921/22 input impedance.

The common-mode voltage of AIN and AIP must be greater than -0.2 V but less than 1 V with respect to GNDA. To meet this requirement, connect GNDA of the Si8921/22 to one side of the R_{SENSE} resistor. In this example, GNDA, R_{SENSE} , the source of Q1, and the drain of Q2 are connected. The ground of the gate driver (Skyworks Si8234 in this circuit) is also commonly connected to the same node.

The Q1 gate driver has a floating supply, 24 V in this example. Since the input and output of the Si8921/22 are galvanically isolated from each other, separate power supplies are necessary on each side. Q3, R3, C3, and D1 make a regulator circuit for powering the input side of the Si8921/22 from this floating supply. D1 establishes a voltage of 5.6 V at the base of Q3. R3 is selected to provide a Zener current of 10 mA for D1. C3 provides filtering at the base of Q3, and the emitter output of Q3 provides approximately 5 V to VDDA. C2 is a bypass capacitor for the supply and should be placed at the VDDA pin with its return trace connecting to the GNDA connection at R_{SENSE} .

C4, the local bypass capacitor for the B-side of Si8921/22, should be placed close to the VDDB supply pin with its return close to GNDB. The output signal at AOP and AON is differential with a nominal gain of 8.2 (Si8921B) or 34.8 (Si8921A) and common mode of 1.4 V.

The outputs are sampled by a differential input ADC. Depending on the sample rate of the ADC, an anti-aliasing filter may be required. A simple anti-aliasing filter can be made from the passive components, R4, C6, and R5. (For the Si8922, Pin 6 and C6 are both grounded, and R5 is removed.)

The characteristics of this filter are dictated by the input topology and sampling frequency of the ADC. However, to ensure the Si8921 outputs are not overloaded, $R4 = R5 > 5$ k Ω and C6 can be calculated using Equation 1:

$$C6 = \frac{1}{2 \times \pi \times (R5 + R6) \times f_{3dB}}$$

Equation 1.

4. Electrical Specifications

Table 4. Absolute Maximum Ratings¹

Parameter	Symbol	Min	Max	Unit
Storage temperature	T_{STG}	-65	150	°C
Ambient temperature under bias	T_A	-40	125	°C
Junction temperature	T_J	—	150	°C
Supply voltage	VDDA, VDDb	-0.5	6.0	V
Input voltage respect to GNDA	VAIP, VAIN	-0.5	VDDA + 0.5	V
Output sink or source current	$ I_O $	—	5	mA
Total power dissipation	P_T	—	212	mW
Lead solder temperature (10 s)		—	260	°C
Human body model ESD rating	HBM	—	6000	V
Charged device model ESD rating	CDM	—	2000	V

1. Permanent device damage may occur if the absolute maximum ratings are exceeded. Functional operation should be restricted to the conditions as specified in the operational sections of this data sheet. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

ESD Handling: Industry-standard ESD handling precautions must be adhered to at all times to avoid damage to this device.

Table 5. Electrical Specifications¹ $T_A = -40$ to $+125$ °C, typical specs at 25 °C with $V_{DDA} = V_{ddb} = 5$ V unless specified differently under Test Condition

Parameter		Symbol	Test Condition	Min	Typ	Max	Unit
Input side supply voltage		VDDA		3.0	—	5.5	V
Input supply current	Si8921A/21B	IDDA	VDDA = 3.3 V	—	4.6	6	mA
	Si8922A/22B	IDDA	VDDA = 3.3 V	—	4.5	6.1	mA
Output side supply voltage		Vddb		3.0	—	5.5	V
Output supply current	Si8921A/21B	IDDB	Vddb = 3.3 V	—	3.5	4.5	mA
	Si8922A/22B	IDDB	Vddb = 3.3 V	—	4.3	5.6	mA
Amplifier bandwidth				—	600	—	kHz
Amplifier Input							
Specified linear input range	Si8921A	VAIP – VAIN		–62.5	—	62.5	mV
	Si8921B			–250	—	250	mV
	Si8922A	VAIP – VAIN		8	—	68.5	mV
	Si8922B			30	—	274	mV
Maximum input voltage before clipping	Si8921A	VAIP – VAIN		—	±77	—	mV
	Si8921B			—	±310	—	mV
	Si8922A			0	77	—	mV
	Si8922B			0	310	—	mV
Common-mode operating range		VCM	A _{IN} ≠ G _{NDA}	–0.2	—	1	V
Input referred offset	Si8921A/21B	VOS	T _A = 25 °C, A _{IP} = A _{IN} = 0	–0.15	±0.04	0.15	mV
	Si8922A/22B	VOS	T _A = 25 °C, A _O = 0.25 V	–0.35	±0.07	0.35	mV
Input offset drift		VOST		–0.3	0.5	3	μV/°C
Differential input impedance	Si8921A/22A	R _{IN}		—	6.3	—	kΩ
	Si8921B/22B			—	21.4	—	kΩ
Differential input impedance drift		R _{IN} _T		—	850	—	ppm/°C
Amplifier Output							
Full-scale output		VAOP – VAON		—	2.5	—	V _{pk}
Gain	Si8921A/22A			—	32.8	—	
	Si8921B/22B			—	8.2	—	
Gain error			T _A = 25 °C	–0.2	±0.06	0.2	%
Gain error drift				–24	–9	0	ppm/°C
Output common mode voltage (Si8921)		(VAOP + VAON)/2		1.34	1.39	1.49	V
Nonlinearity	Si8921A		T _A = 25 °C	–0.04	0.01	0.04	%
	Si8921B		T _A = 25 °C	–0.02	0.003	0.02	%
	Si8922A		T _A = 25 °C	–0.08	0.02	0.08	%
	Si8922B		T _A = 25 °C	–0.04	0.01	0.04	%

Table 5. Electrical Specifications¹ (Continued)T_A = -40 to +125 °C, typical specs at 25 °C with VDDA = VDDB = 5 V unless specified differently under Test Condition

Parameter		Symbol	Test Condition	Min	Typ	Max	Unit
Nonlinearity drift				-16	—	16	ppm/°C
Signal-to-noise ratio	Si8921A	SNR	F _{IN} = 10 kHz, BW = 100 kHz	70	77	—	dB
	Si8921B			75	82	—	dB
	Si8922A			64	71	—	dB
	Si8922B			69	76	—	dB
Signal-to-noise ratio	Si8921A	SNR	F _{IN} = 1 kHz, BW = 10 kHz	—	86	—	dB
	Si8921B			—	91	—	dB
	Si8922A			—	79	—	dB
	Si8922B			—	83	—	dB
Total harmonic distortion	Si8921A	THD	F _{IN} = 1 kHz	—	-85	-74	dB
	Si8921B	THD	F _{IN} = 1 kHz	—	-88	-71	dB
	Si8922A	THD	F _{IN} = 1 kHz	—	-82	-60	dB
	Si8922B	THD	F _{IN} = 1 kHz	—	-85	-63	dB
Power-supply rejection ratio		PSRR	VDDA at dc	—	-100	—	dB
			VDDA at 100 mV and 10 kHz ripple	—	-100	—	dB
			VDDB at DC	—	-100	—	dB
			VDDB at 100 mV and 10 kHz ripple	—	-100	—	dB
Output resistive load	Si8921	R _{LOAD}	Between AON and AOP	5	—	—	kΩ
	Si8922		Between AO and GND	5	—	—	kΩ
Output capacitive load		C _{LOAD}	Each pin to ground	—	—	100	pF
Timing							
Signal delay (Si8921)		t _{PD}	50% to 50%	—	0.8	—	μs
Signal delay (Si8922)		t _{PD}	50% to 50%	—	1	—	μs
Rise time		t _R	10% to 90%	—	0.8	—	μs
Startup time		t _{STARTUP}		—	250	—	μs
Common-mode transient immunity ²		CMTI	AIP = AIN = AGND, VCM = 1500 V	50	75	—	kV/μs

1. Performance is assured only under the conditions listed in this table and is not invariant over the full operating or storage temperature ranges. Operation at elevated temperatures may reduce reliability of the device.

2. An analog CMTI failure is defined as an output error of more than 100 mV persisting for at least 1 μs.




Figure 6. Common-Mode Transient Immunity Characterization Circuit

4.1. Typical Performance Characteristics




Figure 7. Nonlinearity (%) vs. Temperature (°C)




Figure 8. Nonlinearity (%) vs. VDDA Supply (V)




Figure 9. Si8921B Nonlinearity (%) vs. Input Signal Amplitude (mV)




Figure 10. Si8921A Nonlinearity (%) vs. Input Signal Amplitude (mV)




Figure 11. Si8922B Nonlinearity (%) vs. Input Signal Amplitude (mV)




Figure 12. Si8922A Nonlinearity (%) vs. Input Signal Amplitude (mV)




Figure 13. Signal-to-Noise Ratio (dB) vs. Temperature (°C)




Figure 14. Signal-to-Noise Ratio (dB) vs. VDDA Supply (V)




Figure 15. Si892xB Signal-to-Noise Ratio (dB) vs. Input Signal Amplitude (mV)




Figure 16. Si892xA Signal-to-Noise Ratio (dB) vs. Input Signal Amplitude (mV)




Figure 17. Signal-to-Noise Ratio (dB) vs. Input Signal Frequency (kHz)




Figure 18. Si8921 Output Voltage (V) vs. Input Voltage (V)




**Figure 19. Total Harmonic Distortion (dB)
vs. Temperature (°C)**




**Figure 20. Total Harmonic Distortion (dB)
vs. VDDA Supply (V)**




**Figure 21. Si892xB Total Harmonic Distortion (dB)
vs. Input Signal Amplitude (mV)**




**Figure 22. Si892xA Total Harmonic Distortion (dB)
vs. Input Signal Amplitude (mV)**




**Figure 23. Total Harmonic Distortion (dB)
vs. Input Signal Frequency (kHz)**




**Figure 24. Power Supply Rejection Ratio
vs. Power Supply Frequency (kHz)**




Figure 25. Input Offset (mV) vs. Temperature (°C)




Figure 26. Input Offset (mV) vs. VDDA Supply (V)




Figure 27. Gain Error (%) vs. Temperature (°C)




Figure 28. Gain Error (%) vs. VDDA Supply (V)




Figure 29. Amplifier Bandwidth




Figure 30. Common-Mode Rejection Ratio (dB) vs. Input Frequency (kHz)




Figure 31. IDDA (mA) vs. Temperature (°C)




Figure 32. IDDB (mA) vs. Temperature (°C)




Figure 33. Si8921B High-to-Low Step Response




Figure 34. Si8921B Low-to-High Step Response




Figure 35. Si8921A High-to-Low Step Response




Figure 36. Si8921A Low-to-High Step Response




Figure 37. Si8922B High-to-Low Step Response




Figure 38. Si8922B Low-to-High Step Response




Figure 39. Si8922A High-to-Low Step Response




Figure 40. Si8922A Low-to-High Step Response

4.2. Thermal Characteristics

Table 6. Thermal Characteristics

Parameter	Symbol	WB Stretched SOIC-8	NB SOIC-8	Unit
IC junction-to-ambient thermal resistance	θ_{JA}	90	112	°C/W




Figure 41. WB Stretched SOIC-8 Safety Current vs. Ambient Temperature Derating Curve




Figure 42. NB SOIC-8 Safety Current vs. Ambient Temperature Derating Curve

4.3. Safety Certifications and Specifications

Table 7. Regulatory Information¹

CSA
The Si89xx is certified under CSA. For more details, see Master Contract File 232873.
62368-1: Rated up to 600 V _{RMS} reinforced insulation working voltage; rated up to 1000 V _{RMS} basic insulation working voltage.
60601-1: Rated up to 250 V _{RMS} working voltage and two means of patient protection (MOPP).
VDE
The Si89xx is certified under VDE. For more details, see File 5028467.
60747-17: Rated up to 2121 V _{peak} for reinforced insulation working voltage.
UL
The Si89xx is certified under UL1577 component recognition program. For more details, see File E257455.
Rated up to 5000 V _{RMS} V _{ISO} isolation voltage for basic protection.
CQC
The Si89xx is certified under GB4943.1.
Rated up to 250 V _{RMS} reinforced insulation working voltage at 5000 meters tropical climate.

1. For more information, see Section 6. "Ordering Information"

Table 8. Insulation and Safety-Related Specifications

Parameter	Symbol	Test Condition	Value		Unit
			WB Stretched SOIC-8	NB SOIC-8	
Nominal external air gap (clearance) ^{1,2,3}	CLR		8.5	4.0	mm
Nominal external tracking (creepage) ^{1,2,3}	CRP		8.5	4.0	mm
Minimum internal gap (internal clearance)	DTI		0.036	0.036	mm
Tracking resistance	CTI or PTI	IEC60112	Up to 600	Up to 600	V _{RMS}

1. CSA certifies the clearance and creepage limits listed in this table.
2. UL does not impose a clearance and creepage minimum for component-level certifications.
3. VDE certifies the clearance and creepage limits as: NB SOIC-8 ≥ 4.0 mm, WB Stretched SOIC-8 ≥ 8.5 mm.

Table 9. IEC 60664-1 Ratings

Parameter	Test Conditions	Specification	
		WB Stretched SOIC-8	NB SOIC-8
Material group		I/II	I/II
Overvoltage category	Rated mains voltage $\leq 150 V_{RMS}$	I-IV	I-IV
	Rated mains voltage $\leq 300 V_{RMS}$	I-IV	I-III
	Rated mains voltage $\leq 600 V_{RMS}$	I-IV	I-II
	Rated mains voltage $\leq 1000 V_{RMS}$	I-III	I

Table 10. IEC 60747-17 Insulation Characteristics¹

Parameter	Symbol	Test Condition	Characteristic		Unit
			WB Stretched SOIC-8	NB SOIC-8	
Maximum working isolation voltage	V_{IOWM}	According to Time-Dependent Dielectric Breakdown (TDDb) Test	1500	445	V_{RMS}
Maximum repetitive isolation voltage	V_{IORM}	According to Time-Dependent Dielectric Breakdown (TDDb) Test	2121	630	V_{peak}
Apparent charge	q_{pd}	Method b: At routine test (100% production) and preconditioning (type test); $V_{ini} = 1.2 \times V_{IOTM}$, $t_{ini} = 1$ s; $V_{pd(m)} = 1.875 \times V_{IORM}$, $t_m = 1$ s (method b1) or $V_{pd(m)} = V_{ini}$, $t_m = t_{ini}$ (method b2)	≤ 5	≤ 5	pC
Maximum transient isolation voltage	V_{IOTM}	$V_{TEST} = V_{IOTM}$, $t = 60$ s (qualification); $V_{TEST} = 1.2 \times V_{IOTM}$, $t = 1$ s (100% production)	7070	3535	V_{peak}
Maximum surge isolation voltage	V_{IOSM}	Tested in oil with $\geq 1.3 \times V_{IMP}$, 10 kV minimum, and 1.2 μ s/50 μ s profile (qualification)	10400	10400	V_{peak}
Maximum impulse voltage	V_{IMP}	Tested in air with 1.2 μ s/50 μ s profile	8000	5000	V_{peak}
Capacitance (input-output) ²	C_{IO}	$f = 1$ MHz	1	1	pF
Isolation resistance ²	R_{IO}	$T_A = 25$ °C, $V_{IO} = 500$ V	$>10^{12}$	$>10^{12}$	Ω
		$T_A = 125$ °C, $V_{IO} = 500$ V	$>10^{11}$	$>10^{11}$	Ω
	R_{IO_S}	$T_A = T_S$, $V_{IO} = 500$ V	$>10^9$	$>10^9$	Ω
Pollution degree			2	2	
Climatic category			40/125/21	40/125/21	

1. This coupler is suitable for "reinforced insulation" only within the safety limiting values. Compliance with the safety limiting values shall be ensured by means of suitable protective circuits.
2. To determine resistance and capacitance, the device is converted into a two-terminal device. Pins on Side A are shorted together to form the first terminal, and pins on Side B are shorted together to form the second terminal. The parameters are then measured between these two terminals.

Table 11. IEC 60747-17 Safety Limiting Values¹

Parameter	Symbol	Test Condition	Characteristic	Unit
Safety temperature	T_S		150	°C
Safety input, output or supply current (WB stretched SOIC-8)	I_S	$\theta_{JA} = 90\text{ }^{\circ}\text{C/W}$ $V_{DD} = 5.5\text{ V}$ $T_J = 150\text{ }^{\circ}\text{C}$ $T_A = 25\text{ }^{\circ}\text{C}$	253	mA
		$\theta_{JA} = 90\text{ }^{\circ}\text{C/W}$ $V_{DD} = 3.6\text{ V}$ $T_J = 150\text{ }^{\circ}\text{C}$ $T_A = 25\text{ }^{\circ}\text{C}$	386	mA
Safety input, output or supply current (NB SOIC-8)	I_S	$\theta_{JA} = 112\text{ }^{\circ}\text{C/W}$ $V_{DD} = 5.5\text{ V}$ $T_J = 150\text{ }^{\circ}\text{C}$ $T_A = 25\text{ }^{\circ}\text{C}$	203	mA
		$\theta_{JA} = 112\text{ }^{\circ}\text{C/W}$ $V_{DD} = 3.6\text{ V}$ $T_J = 150\text{ }^{\circ}\text{C}$ $T_A = 25\text{ }^{\circ}\text{C}$	310	mA
Safety input, output or total power (WB stretched SOIC-8)	P_S	$\theta_{JA} = 90\text{ }^{\circ}\text{C/W}$ $T_J = 150\text{ }^{\circ}\text{C}$ $T_A = 25\text{ }^{\circ}\text{C}$	1389	mW
Safety input, output or total power (NB SOIC-8)	P_S	$\theta_{JA} = 112\text{ }^{\circ}\text{C/W}$ $T_J = 150\text{ }^{\circ}\text{C}$ $T_A = 25\text{ }^{\circ}\text{C}$	1116	mW

1. Maximum value allowed in the event of a failure. Refer to the derating curves Figure 41, “WB Stretched SOIC-8 Safety Current vs. Ambient Temperature Derating Curve,” on page 18 and Figure 42, “NB SOIC-8 Safety Current vs. Ambient Temperature Derating Curve,” on page 18.

Table 12. UL 1577 Insulation Characteristics

Parameter	Symbol	Test Condition	Characteristic		Unit
			WB Stretched SOIC-8	NB SOIC-8	
Maximum withstanding isolation voltage	V_{ISO}	$V_{TEST} = V_{ISO}$, $t = 60\text{ s}$ (qualification); $V_{TEST} = 1.2 \times V_{ISO}$, $t = 1\text{ s}$ (100% production)	5000	2500	V_{RMS}
Primary-side current rating		$V_{DD} = 5.5\text{ V}$, $T_A = 25\text{ }^{\circ}\text{C}$ (qualification)	6.9	6.9	mA
Primary-side power rating			49.5	49.5	mW
Secondary-side current rating			10.75	10.75	mA
Secondary-side power rating			59	59	mW

5. Package and Handling Information

Since the device package is sensitive to moisture absorption, it is baked and vacuum packed before shipping. Instructions on the shipping container label regarding exposure to moisture after the container seal is broken must be followed. Otherwise, problems related to moisture absorption may occur when the part is subjected to high temperature during solder assembly.

The Si8921 and Si8922 devices with an -IS and -AS suffix are rated to Moisture Sensitivity Level 2 (MSL2) at 260 °C. Devices with an -IS4 and -AS4 suffix are rated to Moisture Sensitivity Level 2A (MSL2A) at 260 °C.

All devices can be used for lead or lead-free soldering. For additional information, refer to Skyworks Application Note, "PCB Design and SMT Assembly/Rework Guidelines," Document Number 101752.

Care must be taken when attaching this product, whether it is done manually or in a production solder reflow environment. Refer to Standard SMT Reflow Profiles: JEDEC Standard J-STD-020.

5.1. 8-Pin, Wide-Body Stretched SOIC Top Marking




Figure 43. Si8921 Typical Package Marking, 8-Pin Wide Body Stretched SOIC

Table 13. 8-Pin Wide Body Stretched SOIC Top Marking Explanation

Line 1	Part Number	Si892x Isolator Amplifier Series X = Base part number 1 = Differential output 2 = Single-ended output S = Specified linear input range A = ± 62.5 mV for Si8921, 8 to 68.5 mV for Si8922 B = ± 250 mV for Si8921, 30 to 274 mV for Si8922 V = Insulation rating D = 5.0 kV_{RMS}
Line 2	TTTTTT	Manufacturing code The first character is a letter in the range N through Z to indicate Automotive Grade
Line 3	YY = Year WW = Work Week Circle = 43 mils diameter left justified	Year and work week

5.2. 8-Pin, Narrow-Body SOIC Top Marking




Figure 44. Si8921/22 Typical Package Marking, 8-Pin Narrow Body SOIC

Table 14. 8-Pin Narrow Body SOIC Top Marking Explanation

Line 1	Part Number	Si892x Isolator Amplifier Series X = Base part number 1 = Differential output 2 = Single-ended output S = Specified linear input range A = ± 62.5 mV for Si8921, 8 to 68.5 mV for Si8922 B = ± 250 mV for Si8921, 30 to 274 mV for Si8922 V = Insulation rating B = 2.5 kV_{RMS}
Line 2	CC = Country of origin ISO code abbreviation	
	YY = Year WW = Work Week	Year and work week
Line 3	TTTTT - Manufacturing code Circle = 19.7 mils diameter left justified	Manufacturing code The first character is a letter in the range N through Z to indicate Automotive Grade

5.3. 8-Pin, Wide-Body Stretched SOIC Package




Figure 45. 8-Pin Wide Body Stretched SOIC Package

Table 15. 8-Pin Wide Body Stretched SOIC Package Dimensions^{1,2,3}

Dimension	Millimeters	
	Min	Max
A	2.49	2.79
A1	0.36	0.46
b	0.30	0.51
c	0.20	0.33
D	5.74	5.94
E	11.25	11.76
E1	7.39	7.59
e	1.27 BSC	
L	0.51	1.02
h	0.25	0.76
θ	0°	8°
aaa		0.25
bbb		0.25
ccc		0.10

1. All dimensions shown are in millimeters (mm) unless otherwise noted.
2. Dimensioning and tolerancing per ANSI Y14.5M-1994.
3. Recommended reflow profile per JEDEC J-STD-020C specification for small body, lead-free components.

5.4. 8-Pin, Narrow-Body SOIC Package




Figure 46. 8-Pin Narrow Body SOIC Package

Table 16. 8-Pin Narrow Body SOIC Package Dimensions^{1,2,3,4,5}

Dimension	Symbol	Min	Max
Overall height	A	—	1.75
Stand off	A1	0.10	0.25
Lead width	b	0.33	0.51
L/F thickness	c	0.19	0.25
Body size	D	4.80	5.00
	E	5.80	6.20
	E1	3.80	4.00
Lead pitch	e	1.27 BSC	
Lead length	L	0.40	1.27
Gauge plane	L2	0.25 BSC	
Corner chamfer	h	0.25	0.50
Foot angle	θ	0°	8°
Lead edge tolerance	aaa	0.10	
Lead offset	bbb	0.20	
Coplanarity	ccc	0.10	

1. All linear dimensions are in millimeters.
2. Dimensioning and tolerancing per ANSI Y14.5M.
BSC: Basic dimension. Theoretically exact shown without tolerance.
REF: Reference dimension. Usually without tolerance; for information purposes only.
3. Dimension D does not include mold flash, protrusions, or gate burrs, which shall not exceed 0.15 mm per end. Dimension E1 does not include interlead flash or protrusion, which shall not exceed 0.25 mm per side.
4. This drawing conforms to the JEDEC Solid State Outline MS-137, Variation AB.
5. Recommended reflow profile per JEDEC J_STD_020 specification for small body, lead-free components.

5.5. 8-Pin, Wide-Body Stretched SOIC Land Pattern




Figure 47. 8-Pin Wide Body Stretched SOIC Land Pattern

Table 17. 8-Pin Wide Body Stretched SOIC Land Pattern Dimensions

Dimension	mm	Notes
C1	10.60	General 1. All dimensions shown are at Maximum Material Condition (MMC). Least Material Condition (LMC) is calculated based on a fabrication allowance of 0.05 mm. 2. This land pattern design is based on the IPC-7351 guidelines. Solder Mask Design 1. All metal pads are to be non-solder-mask-defined (NSMD). 2. Clearance between the solder mask and the metal pad is to be 60 µm minimum, all the way around the pad. Stencil Design 1. A stainless steel, laser-cut and electro-polished stencil with trapezoidal walls should be used to assure good solder paste release. 2. The stencil thickness should be 0.125 mm (5 mils). 3. The ratio of stencil aperture to land pad size should be 1:1 for all perimeter pads. Card Assembly 1. A No-Clean, Type-3 solder paste is recommended. 2. The recommended card reflow profile is per the JEDEC/IPC J-STD-020 specification for small body components.
E	1.27	
X1	0.60	
Y1	1.85	

5.6. 8-Pin Wide Body Stretched SOIC Tape and Reel Information




Figure 48. Wide Body Carrier Tape Information




Figure 49. Wide Body Reel Information

5.7. 8-Pin, Narrow-Body SOIC Land Pattern




Figure 50. 8-Pin Narrow Body SOIC Land Pattern

Table 18. 8-Pin Narrow Body SOIC Land Pattern Dimensions^{1,2}

Dimension	mm
C1	5.40
E	1.27
X1	0.60
Y1	1.55

1. All feature sizes shown are at Maximum Material Condition (MMC) and a card fabrication tolerance of 0.05 mm is assumed.
2. This land pattern design is based on IPC-7351 pattern SOIC127P600X173-8N for Density Level B (Median Land Protrusion).

5.8. 8-Pin Narrow Body SOIC Tape and Reel Information




Figure 51. Narrow Body Carrier Tape Information




Figure 52. Narrow Body Reel Information

6. Ordering Information

6.1. Industrial and Automotive Grade Ordering Part Numbers (OPNs)

Industrial-grade devices (part numbers with an “-I” in their suffix) are built using well-controlled, high-quality manufacturing flows to ensure robustness and reliability. Qualifications are compliant with JEDEC, and defect reduction methodologies are used throughout definition, design, evaluation, qualification, and mass production steps.

Automotive-grade devices (part numbers with an “-A” in their suffix) are built using automotive-specific flows at all steps in the manufacturing process to ensure robustness and low defectivity. These devices are supported with AIAG-compliant Production Part Approval Process (PPAP) documentation, and feature International Material Data System (IMDS) and China Automotive Material Data System (CAMDS) listings. Qualifications are compliant with AEC-Q100, and a zero-defect methodology is maintained throughout definition, design, evaluation, qualification, and mass-production steps.

Table 19. Si8921/22 Ordering Information

Ordering Part Number ^{1, 2, 3}	Automotive Ordering Part Number ^{1, 2, 3, 4, 5}	Ordering Options			
		Specified Input Range	Isolation Rating	Output	Package Type
Si8921AD-IS4	Si8921AD-AS4	±62.5 mV	5.0 kV _{RMS}	Differential	WB stretched SOIC-8
Si8921BD-IS4	Si8921BD-AS4	±250 mV	5.0 kV _{RMS}	Differential	WB stretched SOIC-8
Si8921AB-IS	Si8921AB-AS	±62.5 mV	2.5 kV _{RMS}	Differential	NB SOIC-8
Si8921BB-IS	Si8921BB-AS	±250 mV	2.5 kV _{RMS}	Differential	NB SOIC-8
Si8922AD-IS4	Si8922AD-AS4	8 to 68.5 mV	5.0 kV _{RMS}	Single-ended	WB stretched SOIC-8
Si8922BD-IS4	Si8922BD-AS4	30 to 274 mV	5.0 kV _{RMS}	Single-ended	WB stretched SOIC-8
Si8922AB-IS	Si8922AB-AS	8 to 68.5 mV	2.5 kV _{RMS}	Single-ended	NB SOIC-8
Si8922BB-IS	Si8922BB-AS	30 to 274 mV	2.5 kV _{RMS}	Single-ended	NB SOIC-8

1. All packages are RoHS-compliant.
2. “SI” and “Si” are used interchangeably.
3. An “R” at the end of the part number denotes tape and reel packaging option.
4. Automotive-grade devices (“-A” suffix) are identical in construction materials, topside marking, and electrical parameters to their Industrial Grade (“-I suffix”) version counterparts. Automotive-Grade products are produced utilizing full automotive process flows and additional statistical process controls throughout the manufacturing flow. The Automotive-Grade part number is included on shipping labels.
5. In the top markings of each device, the Manufacturing Code represented by “TTTTT” contains as its first character a letter in the range N through Z to indicate Automotive Grade.

7. Revision History

Revision	Date	Description
E	June, 2026	- Updated formatting. - Updated 3.1. "Fail-Safe and Low-Power Modes". - Removed reference to low-power mode when VDDDB supply is lost. - Removed "pending" and updated tables in 4.3. "Safety Certifications and Specifications" to reflect content required by certification bodies. - Updated Table 7. "Regulatory Information". - Updated Table 8. "Insulation and Safety-Related Specifications". - Updated Table 9. "IEC 60664-1 Ratings". - Updated Table 10. "IEC 60747-17 Insulation Characteristics". - Updated Table 11. "IEC 60747-17 Safety Limiting Values". - Updated Table 12. "UL 1577 Insulation Characteristics". - Added tape and reel information.
D	September, 2025	- Updated 8-Pin, narrow-body SOIC package. - Removed tape and reel information.
C	September, 2023	- Updated regulatory information. - Updated absolute maximum Note 1. - Removed unneeded minimum IDD specifications.
B	May, 2023	- Reformatted to new standards. - Added new text for automotive grade products, AEC-Q100 qualification. - Added MSL ratings and tape and reel information. - Updated THD specifications. - Updated specified linear input range. - Updated block diagrams on page 1. - Updated Si8922 pin description.
A	December, 2022	Updated decimal-based revision number to alphanumeric code.
0.9	September, 2022	- Updated safety approvals. - Updated minimum supply currents in electrical specifications. - Updated regulatory information.
0.8	June, 2021	- Added Automotive OPNs and updated specified input range in ordering guide. - Updated current sense application figure. - Added linearity minimum specification to Table 4.1 Electrical Specifications.
0.7	April, 2020	- Numerous clarifications throughout. - Updated electrical specifications after full characterization. - Changed Si8922 Pin 6 from NC to GND.
0.51	June, 2019	- Added section for automotive grade OPNs. - Corrected error in specified linear input range. - Changed DTI Specification. - Corrected Si8922 pin diagram. - Updated supply currents.
0.5	March, 2019	- Updated specifications. - Added narrow body SOIC-8 package.
0.1	February, 2018	Initial release.

Copyright © 2018-2023, 2025-2026, Skyworks Solutions, Inc. All Rights Reserved.

Information in this document is provided in connection with Skyworks Solutions, Inc., and its subsidiaries ("Skyworks") products or services. These materials, including the information contained herein, are provided by Skyworks as a service to its customers and may be used for informational purposes only by the customer. Skyworks assumes no responsibility for errors or omissions in these materials or the information contained herein. Skyworks may change its documentation, products, services, specifications or product descriptions at any time, without notice. Skyworks makes no commitment to update the materials or information and shall have no responsibility whatsoever for conflicts, incompatibilities, or other difficulties arising from any future changes.

No license, whether express, implied, by estoppel or otherwise, is granted to any intellectual property rights by this document. Skyworks assumes no liability for any materials, products or information provided hereunder, including the sale, distribution, reproduction or use of Skyworks products, information or materials, except as may be provided in Skyworks' Terms and Conditions of Sale.

THE INFORMATION IN THIS DOCUMENT AND THE MATERIALS AND PRODUCTS DESCRIBED THEREIN ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, WHETHER EXPRESS, IMPLIED, STATUTORY, OR OTHERWISE, INCLUDING FITNESS FOR A PARTICULAR PURPOSE OR USE, MERCHANTABILITY, PERFORMANCE, QUALITY OR NON-INFRINGEMENT OF ANY INTELLECTUAL PROPERTY RIGHT; ALL SUCH WARRANTIES ARE HEREBY EXPRESSLY DISCLAIMED. SKYWORKS DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. SKYWORKS SHALL NOT BE LIABLE FOR ANY DAMAGES, INCLUDING BUT NOT LIMITED TO ANY SPECIAL, INDIRECT, INCIDENTAL, STATUTORY, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS THAT MAY RESULT FROM THE USE OF THE MATERIALS OR INFORMATION, WHETHER OR NOT THE RECIPIENT OF MATERIALS HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Skyworks products are not designed, intended, authorized, or warranted for use or inclusion in life support or life endangering applications, devices, or systems where failure or inaccuracy might cause death or personal injury. Skyworks customers agree not to use or sell the Skyworks products for such applications, and further agree to, without limitation, fully defend, indemnify, and hold harmless Skyworks and its agents from and against any and all actions, suits, proceedings, costs, expenses, damages, and liabilities including attorneys' fees arising out of or in connection with such improper use or sale.

Skyworks assumes no liability for applications assistance, customer product design, or damage to any equipment resulting from the use of Skyworks products outside of Skyworks' published specifications or parameters. Customers are solely responsible for their products and applications using the Skyworks products.

"Skyworks" and the Skyworks Starburst logo are registered trademarks of Skyworks Solutions, Inc., in the United States and other countries. Third-party brands and names are for identification purposes only and are the property of their respective owners. Additional information, including relevant terms and conditions, posted at www.skyworksinc.com, are incorporated by reference.