


BNPGB1010402KR

ESD Protection Diode

Features

- The best ESD protection for high speed, low voltage applications
- RoHS compliant and halogen free
- Ultra low capacitance, 0.05 pF (typ.)
- Low leakage current (<10nA)
- Fast response time (<1ns)
- Bi-directional, single line protection
- Surface mount

Package



Applications

- Smart Phone/Mobile Internet Device
- Laptop/Desktop Computer
- Antennas
- High Speed Ethernet
- USB 2.0 and USB 3.0
- Lightning and Thunder Bolt Interface

Mechanical Data

- Surface mount
- RoHS Compliant
- Halogen Free

Ordering information

Order code	Package	Base qty	Delivery mode
BNPGB1010402KR	DFN1006	10k	Tape and reel

Absolute Maximum Rating

Rating	Symer	Value	Units
ESD per IEC 61000-4-2 (Contact)	V_{ESD}	± 8	KV
ESD per IEC 61000-4-2 (Air)		± 15	
Lead Soldering Temperature	T_L	260(10seconds)	$^{\circ}C$
Operating Temperature	T_O	-40 to + 125	$^{\circ}C$
Storage Temperature	T_{stg}	-55 to + 125	$^{\circ}C$

**BORN SEMICONDUCTOR, INC. ALL
RIGHT RESERVED**

Specifications are subject to change without notice.

Please refer to <http://www.born-tw.com> for current information.

Revision: 2022-Jan-1-B




BNPGB1010402KR

ESD Protection Diode

Electrical Characteristics

Part NO.	Working Voltage	Typical ESD Trigger Voltage	Typical ESD Clamping Voltage at 60ns	Leakage Current (at Initial State)	Cap. Value @10MHz
Symbol	$V_{DC(max.)}$	$V_{trigger(typ.)}$	$V_C(typ.)$	I_{LDC}	$C(Typ.)$
Unit	V	V	V	μA	pF
BNPGB1010402KR	12	450	40	<0.01	0.05

ESD Clamping Test



BNPGB1010402KR

ESD Protection Diode

Figure 1: ESD Clamping Test Waveform




Figure 2: ESD Waveform after Clamping






Figure 3: Capacitance VS Frequency




Use of circuit



BNPGB1010402KR


ESD Protection Diode

Outline Drawing - DFN1006



SYMBOL	MILLIMETERS		
	MIN.	Typ.	MAX.
L	0.90	1.00	1.10
W	0.42	0.52	0.62
P	0.15	0.25	0.35
H	0.25	0.38	0.45


Packaging Tape - DFN1006



SYMBOL	MILLIMETER
A0	0.71±0.05
B0	1.11±0.05
d0	1.5 ^{+0.1} ₋₀
d1	0.50±0.05
E	1.75±0.10
F	3.50±0.05
K0	0.56±0.05
P	2.00±0.05
P0	4.00±0.10
P1	2.00±0.05
W	8.00 ^{+0.03} _{-0.01}
T	0.2±0.015

Packaging Reel

SECTION:K-K



SYMBOL	MILLIMETER
A	178±1
B	3.5±0.2
C	14.3±0.2
D	9.8 ⁺² ₋₁
E	54.5±0.5
F	12.4±0.2
T1	1.0±0.2
Quantity	10000PCS

**BORN SEMICONDUCTOR, INC. ALL
RIGHT RESERVED**

Specifications are subject to change without notice.

Please refer to <http://www.born-tw.com> for current information.

Revision: 2022-Jan-1-B

