
CONNECTORS


Operation: Push-Pull



ROHS

LTEM NO.:TF-005
(MEMORY-CARD-SOCKETS)

Unit:mm



Technical parameter

PROJECT \ LEVEL		A[better product]	B[average product]	C[low product]
Electrical Properties	Initial Contact Resistance	30mΩ max.	30mΩ max.	no data!
	Contact Resistance	100mΩ min.100V DC Skey/PD: 50mΩ min.100V DC		
	Withstand Voltage	300V AC for 1min	250 V AC for 1min	
Durable Performance	There No Load	8,000 Cycles	**7,000 Cycles**	no data!
	Rated Load	6,500 Cycles 50mΩ max.	**5,000 Cycles 30mΩ max.**	no data!
Insertion Force		4.0Kgf MAX (Springback:)		

表面貼裝 SMT


側向導入 LATERAL

精密部品 NICETY

可靠 STABILIZE

適合環保 RoHS

CIRCUIT BOARD SIZE
(Vertical view)



邀您使用(微信)小程序
硕方电子开关&连接器选型手册
手机扫码即可进入...

PIN Assignment

TF CARD Pin DESIGN			
Pin No.	Pin NAME	Type	Description
P①	DAT2	I/0/PP	Date Line[Bit 2]
P②	CD/DAT3	I/0/PP	Card Detect Date Lin(BIT3)
P③	CMD	PP	Command Response
P④	VDD	S	Supply voltage
P⑤	CLX	I	Clock
P⑥	Vss	S	Supply voltage ground
P⑦	DAT 0	I/0/PP	Date Line [Bit 0]
P⑧	DAT 1	I/0/PP	Date Line [Bit 1]

本品不屬於危害性廢棄物,須丟棄時可以委託回收商予以回收再生處理。Products do not belong to hazardous waste,When waste can recycling processing

運送時本產品不要直接與水、酸鹼性化學物質接觸,或放置於含有以上氣體環境中,並且需要注意會有滑落、側翻的危險發生；運輸過程中不能有碰撞或者擠壓,須保證溫度與濕度適中[常溫 25℃,濕度在 50℃以內],不可導致材料變形或氧化。

注記 NOTICE

1. 硕方電子公司擁有最終解釋權； The company reserves the right of final interpretation；
2. 文件禁止外洩、轉載； Leaked and reproduced prohibited；
3. 未經授權修改無效。 Modify is invalid.