

V_{DS}	$R_{DS(on)Typ}$	I_D@25℃
800V	240mΩ	10A





RoHS REACH HF

Applications:

- LED driver
- PD charger
- PC adapter
- Air-conditioning
- E-bike charger

Features:

- Revolutionary semiconductor material Silicon Carbide
- High blocking voltage with low on-resistance
- High-speed switching with very low switching losses
- High-speed and high robust intrinsic body diode

Ordering Information

Part Number	Package	Marking	Packing	Qty.
RSM080240BF	TO-220F	RSM080240BF	Tube	50 PCS

Maximum Ratings （TJ= 25℃ unless otherwise specified）

Symbol	Parameter	Value	Unit	Test Conditions
V_{DS}	Drain - Source Voltage	800	V	V_{GS}=0V,I_D=250μA
V_{GS}	Gate - Source Voltage	-10/+22	V	Absolute maximum values
V_{GSOP}	Recommended Operation Voltage of Gate to Source	0/+18	V	Recommended operational values
I_D	Continuous Drain Current	10 8.5	A	T_C =25℃ T_C =100℃
I_{DM}	Pulsed Drain Current	18	A	T_C =25℃
E_{AS}	Single Pulse Avalanche Energy L=0.5mH,I_{AS}=8.4A,V_{DD}=50V,V_{GS}=15 V	17	mJ	
P_D	Power Dissipation	25	W	T_C =25℃
T_J, T_{stg}	Operating Junction and StorageTemperature	-55 to + 175	℃	

preliminary

Copyright Reasunos

Electrical Characteristics (TJ= 25℃ unless otherwise specified)

Symbol	Parameter	Min.	Typ.	Max.	Unit	Test Conditions	Note
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage	800			V	V_{GS}=0V,I_D=250μA	
$V_{GS(th)}$	Gate Threshold Voltage	2.7	3.5		V	V_{GS}= V_{DS}, I_D=3.5mA	
I_{DSS}	Zero Gate Voltage Drain Current			20	μA	V_{DS}=800V, V_{GS}=0V	
I_{GSS}	Gate-Source Leakage Current			250	nA	V_{GS}=22V, V_{DS}=0V	
$R_{DS(on)}$	Drain-Source on-state Resistance		300	390	mΩ	V_{GS}=15V, I_D =5A	
			240	360		V_{GS}=18V, I_D =5A	
C_{iss}	Input Capacitance		228		pF	V_{GS}=0V, V_{DS}=400V f=1MHz,T_j=25℃	
C_{oss}	Output Capacitance		17				
C_{rss}	Reverse Transfer Capacitance		1.4				
gfs	Transconductance		3.5		S	V_{DS}=20V,I_D=5A	
R_G	Internal Gate Resistance		26		Ω	f=1MHz,V_{AC}=25mV	
Q_g	Total Gate Charge		8.8		nC	V_{DS}=400V V_{GS}=0/+15V I_D=5A	
Q_{gs}	Gate to Source Charge		3.3				
Q_{gd}	Gate to Drain Charge		1.2				
$t_{d(on)}$	Turn-On Delay Time		16.5 14.9		ns	V_{DD}=400V V_{GS} =0/15V L=600μH I_D=5A $R_{G(on)}$=4.3Ω $R_{Goff)}$=4.3Ω	T_j=25℃ T_j=175℃
t_r	Rise Time		11.3 9.5				T_j=25℃ T_j=175℃
$t_{d(off)}$	Turn-Off Delay Time		21.2 23.9				T_j=25℃ T_j=175℃
t_f	Fall Time		12.7 12.5				T_j=25℃ T_j=175℃
E_{on}	Turn−On Switching Loss		47.6 45.1		μJ		T_j=25℃ T_j=175℃
E_{off}	Turn−Off Switching Loss		4.0 3.8				T_j=25℃ T_j=175℃
E_{tot}	Total Switching Energy		51.6 48.9				T_j=25℃ T_j=175℃

preliminary

Copyright Reasunos

Reverse Diode Characteristics (TJ= 25℃ unless otherwise specified)

Symbol	Parameter	Typ.	Max	Unit	Test Conditions	Note
V_{SD}	Diode Forward Voltage	3.5 3.0		V	V_{GS}=0V, I_{SD} =2.5A	T_j=25℃ T_j=175℃
I_S	Continuous Diode Forward Current	9.7 5.7		A	T_C= 25℃ T_C= 100℃	
t_{rr}	Reverse Recovery time	10.9 10		ns	V_{GS}=0V,I_{SD}=5A V_{DS}=400V,T_j=25℃ di/dt=1.1KA/us	T_j=25℃ T_j=175℃
Q_{rr}	Reverse Recovery Charge	28 30		nC		T_j=25℃ T_j=175℃
I_{rrm}	Peak Reverse Recovery Current	3.9 4.5		A		T_j=25℃ T_j=175℃
E_{rr}	Reverse Recovery Energy	0.22 0.33		μJ		T_j=25℃ T_j=175℃

Thermal Characteristics (TJ= 25℃ unless otherwise specified)

Symbol	Parameter	Typ.	Max.	Unit	Test Conditions
$R_{\theta JC}$	Thermal Resistance from Junction to Case	5.9		℃/W	


preliminary

Copyright Reasunos

Typical Feature Curve


Safe operating area (SOA)

$R_{th(j-c)}$ =3.1 °C/W, Single Pulse, T_{VJ} = 25°C



Power dissipation as a function of case temperature limited by bond wire


$P_D = f(T_C)$



Typical output characteristic, V_{GS} as parameter

$I_{DS} = f(V_{DS})$


T_{VJ} = -55 °C



Typical output characteristic, V_{GS} as parameter

$I_{DS} = f(V_{DS})$

T_{VJ} = 25 °C




pre liminary

Copyright Reasunos

Typical output characteristic, V_{GS} as parameter


$I_{DS} = f(V_{DS})$

$T_{VJ} = 175℃$




Typical on-state resistance as a function of drain current

$R_{DS(on)} = f(I_{DS})$, V_{GS} = 15V



Typical on-state resistance as a function of temperature


$R_{DS(on)} = f(T_{VJ})$, I_{DS} = 5 A



Typical on-state resistance as a function of V_{GS}

$R_{DS(on)} = f(V_{GS})$

I_{DS} = 5 A




preliminary

Copyright Reasunos

Typical transfer characteristic


$I_{DS} = f(V_{GS})$

V_{DS}= 20 V




Typical gate-source threshold voltage as a function of junction temperature

$V_{GS(th)} = f(T_{VJ})$, I_{DS} = 3.5 mA




Typical reverse drain current as function of reverse drain voltage, V_{GS} as parameter

$I_{DS} = f(V_{DS})$, T_{VJ} = -55 °C



Typical reverse drain current as function of reverse drain voltage, V_{GS} as parameter

$I_{DS} = f(V_{DS})$, T_{VJ} = 25 °C




preliminary

Copyright Reasunos


Typical reverse drain current as function of reverse drain voltage, V_{GS} as parameter

$I_{DS} = f(V_{DS})$, T_{VJ} = 175 °C



Typical reverse drain voltage as function of junction temperature


$V_{SD} = f(T_{VJ})$, I_{SD} = 2.5 A



Typical switching energy as a function of junction temperature, 2nd device own body diode: V_{GS} = 0 V

$E = f(T_{VJ})$


V_{DS} = 400 V, $R_{G(ext)}$ = 4.3 Ω, V_{GS} = 0V / 15 V, I_{DS} = 5 A



Typical switching energy losses as a function of gate resistance, 2nd device own body diode: V_{GS} = 0 V

$E = f(R_{G(ext)})$

V_{GS} = 0/15 V, I_{DS} = 5 A, T_{VJ} = 25 °C, V_{DS} = 400 V




preliminary

Copyright Reasunos

Typical switching energy losses as a function of gate resistance, 2nd device own body diode: V_{GS} = 0 V

$E = f(R_{G(ext)})$


V_{GS} = 0/15 V, I_{DS} = 5 A, T_{VJ} = 175 °C, V_{DS} = 400 V



Typical switching energy losses as a function of I_{DS}, 2nd device own body diode: V_{GS} = 0 V

$E = f(I_{DS})$


V_{GS} = 0/15 V, $R_{G(ext)}$ = 4.3 Ω, T_{VJ} = 25 °C, V_{DS} = 400 V



Typical switching energy losses as a function of I_{DS}, 2nd device own body diode: V_{GS} = 0 V

$E = f(I_{DS})$


V_{GS} = 0/15 V, $R_{G(ext)}$ = 4.3 Ω, T_{VJ} = 175 °C, V_{DS} = 400 V



Typical switching energy losses as a function of V_{DS}, 2nd device own body diode: V_{GS} = 0 V

$E = f(V_{DS})$

V_{GS} = 0/15 V, $R_{G(ext)}$ = 4.3 Ω, T_{VJ} = 25 °C, I_{DS} = 5 A




preliminary

Copyright Reasunos

Typical switching energy losses as a function of V_{DS}, 2nd device own body diode: V_{GS} = 0 V

$E = f(V_{DS})$


V_{GS} = 0/15 V, $R_{G(ext)}$ = 4.3 Ω, T_{VJ} = 175 °C, I_{DS} = 5 A



Typical gate charge


$V_{GS} = f(Q_G)$, I_{DS} = 5A, V_{DS} = 400V

turn-on pulse



Typical capacitance as a function of drain-source voltage

$C = f(V_{DS})$, V_{GS} = 0V, f = 1MHz




preliminary

Copyright Reasunos

Transient thermal resistance (MOSFET)


($Z_{th(j-c,max)}$ = f(t_p), Parameter D = t_p/T



preliminary

Copyright Reasunos


Package outline drawing(TO-220F Unit: mm)



外形一

Dim.	Min.	Max.
A	9.95	10.36
A1	4.5	5.0
B	2.95	3.25
C	1.25	1.45
D	12.60	13.60
E	0.40	0.60
F	2.8	3.5
G	1.30	1.45
H	(2.54)	
I	(5.08)	
J	4.60	4.75
K	2.45	2.65
L	6.5	6.8
M	15.4	16.0
N	2.25	3.05
O	0.45	0.55
P	0.70	0.90

All Dimensions in millimeter



外形二

Dim.	Min.	Max.
W	9.95	10.36
W1	(2.54)	
W2	0.70	0.90
W3	1.25	1.47
L	15.67	16.07
L1	6.48	6.88
L2	3.2	3.4
L3	12.6	13.6
L4	(3.23)	
T	4.50	4.90
T1	2.34	2.74
T2	2.25	2.95
T3	0.45	0.60
T4	(0.70)	
G	3.08	3.28

All Dimensions in millimeter

preliminary

Copyright Reasunos

Disclaimers:

Reasunos Semiconductor Technology Co.Ltd (Reasunos) reserves the right to make changes without notice in order to improve reliability,function or design and to discontinue any product or service without notice .Customers should obtain the latest relevant information before orders and should verify that such information in current and complete.All products are sold subject to Reasunos's terms and conditions supplied at the time of orderacknowledgement.

Reasunos Semiconductor Technology Co.Ltd warrants performance of its hardware products to the speciffications at the time of sale.Testing,reliability and quality control are used to the extene Reasunos deems necessary to support this warrantee. Except where agreed upon by contr- actual agreement,testing of all parameters of each product is not necessarily performed.

Reasunos Semiconductor Technology Co.Ltd does not assume any liability arising from the use of any product or circuit designs described herein.Customers are responsible for their products and applications using Reasunos's components.To minimize risk,customers must provide adequate design and operating safeguards.

Reasunos Semiconductor Technology Co.Ltd does not warrant or convey any license eith- er expressed or implied under its patent rights,nor the rights of others.Reproduction of inform- ation in Reasunos's data sheeets or data books is permissible only if reproduction is without modification oralteration.Reproduction of this information with any alteration is an unfair and deceptive business practice. Reasunos Semiconductor Technology Co.Ltd is not responsi- ble or liable for such altered documentation.

Resale of Reasunos's products with statements different from or beyond the parameters stated by Reasunos Semiconductor Technology Co.Ltd for that product or service voids all exp- ress or implied warrantees for the associated Reasunos's product or service and is unfair and deceptive business practice. Reasunos Semiconductor Technology Co.Ltd is not responsi- ble or liable for such statements.

preliminary

Life Support Policy:

Reasunos Semiconductor Technology Co.Ltd's Products are not authorized for use as cri- tical components in life support devices or systems without the expressed written approval of Reasunos Semiconductor Technology Co.Ltd.
As used herein:
1. Life support devices or systems are devices or systems which: a.are intended for surgical implant into the human body, b.support or sustain life,
c.whose failuer to when properly used in accordance with instructions for used provided in the laeling,can be reasonably expected to result in significant injury to the user.

2.A critical component is any component of a life support device or system whose failure to system whose failure to perform can be reasonably expected to cause the failure of the life support device or system,or to affect its safety or effectiveness.

Copyright Reasunos