Glass Passivated Surface Mount Bridge Rectifiers

1 General Description

1.1 Features

- Compact, thin profile package design
- Ideal for SMT manufacturing
- Reliable robust construction


REVERSE VOLTAGE
50-1000V
FORWARD CURRENT
4Ampere

1.2 Typical Applications

- Suitable for AC-to-DC bridge full wave rectification for SMPS, LED lighting, adapter, battery charger, home appliances, office equipment, and telecommunication applications.

1.3 Mechanical Data

- Molding compound meets UL 94 V-0 flammability rating, Halogen-free, RoHS-compliant, and commercial grade
- Polarity indicator: As marked on body



2 Maximum Ratings(TA=25℃ Unless otherwise specified)

PARAMETER	SYMBOL	MSB40A	MSB40B	MSB40D	MSB40G	MSB40J	MSB40K	MSB40M	UNIT
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS Bridge Input Voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Output Current at Tc=120℃	$I_{F(AV)}$	4.0							A
Peak Forward Surge Current Single Sine-Wave Superimposed On Rated Load (JEDEC Method)	I_{FSM}	125							A
Rating for fusing (1ms< t<8.3ms)	I^2t	64.8							A^2s
Operating Temperature Range	T_J	-55 to +150							℃
Storage Temperature Range	T_{STG}	-55 to +150							℃
Typical Thermal Resistance(Note2)	$R_{\theta JA}$	25							℃/W
	$R_{\theta JL}$	15							
	$R_{\theta JC}$	8							

Notes:1. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.

2. Thermal Resistance test performed in accordance with JESD-51. Unit mounted on15 mm*12 mm*1.6 mm AL pad attach 195 mm*110 mm*10 mm steel plate

3.The typical data above is for reference only

3 Electrical Characteristics(TA=25℃ Unless otherwise specified)

PARAMETER		SYMBOL	MSB40A	MSB40B	MSB40D	MSB40G	MSB40J	MSB40K	MSB40M	UNIT
Maximum instantaneous Forward Voltage T_J=25℃	1.5A DC	V_F	1							V
	3.0A DC		1.1							
Maximum DC Reverse Current at Rated DC Blocking Voltage	T_J=25℃	I_R	5							μA
	T_J=125℃		500							
Typical Junction Capacitance(Note1)		C_J	35							pF

4 Characteristics Curves(TA=25℃ Unless otherwise specified)

FIG. 1 – FORWARD CURRENT DERATING CURVE




FIG. 2 – MAXIMUM NON-REPETITIVE SURGE CURRENT




FIG.3-TYPICAL FORWARD CHARACTERISTICS




FIG.4 – TYPICAL JUNCTION CAPACITANCE






FIG.5- TYPICAL REVERSE CHARACTERISTICS



5 Package Outline Dimensions



Symbol	UNIT(mm)	
	Min	Max
A	6.50	6.70
B	0.95	1.25
C	7.90	8.60
D	7.20	7.40
E	0.95	1.25
F	5.00	5.20
G	0.95	1.15
H	0.65	1.05
I	2.90	3.10
J	1.30	1.50
K	0.04	0.08
L	0.27	0.40

6 Ordering Information

PACKAGE	UNIT WEIGHT (g)	REEL (pcs)	CARTON (pcs)
MSBL	Approximate 0.37	3000	36000

Disclaimer

1. All information contained in this document is for reference only. Shandong Baocheng Electronics Co.,Ltd reserves the right to revise this document, product specifications and related data at any time without prior notice. Customers shall obtain and confirm the latest product documents and specifications before purchasing or using the products.

2. Under no circumstances shall the Company be liable for any failure or damage caused by the operation of semiconductor devices beyond the maximum rated values.

3. Shandong Baocheng Electronics Co.,Ltd does not warrant the suitability of its products for any specific application and assumes no responsibility for customer's complete machine design or application debugging. Without written approval, products are prohibited from being used as key components of life support equipment. The Company shall not be liable for any consequences arising from unauthorized use.

4. No intellectual property license of Shandong Baocheng Electronics Co.,Ltd is granted, explicitly or implicitly, through this document.