Product Summary

$V_{(BR)DSS}$	$R_{DS(on)TYP}$	I_D
20V	45mΩ@4.5V	2.1A
	60mΩ@2.5V	

合肥矽普半导体
Siliup Semiconductor Technology Co.Ltd
技术 品质 服务
www.siliup.com

Feature

- High power and current handing capability
- Surface mount package

Application

- Battery Switch
- DC/DC Converter

Package



SOT-23

Circuit diagram



Marking



2302B :Device Code

Order Information

Device	Package	Unit/Tape
SP2302BT2	SOT-23	3000

Absolute maximum ratings (Ta=25℃, unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V_{DSS}	20	V
Gate-Source Voltage	V_{GSS}	±10	V
Continuous Drain Current (Ta=25℃)	I_D	2.1	A
Continuous Drain Current (Ta=100℃)	I_D	1.4	A
Pulse Drain Current Tested	I_{DM}	8.4	A
Power Dissipation (Ta=25℃)	P_D	0.5	W
Power Dissipation (Ta=100℃)	P_D	0.2	W
Thermal Resistance Junction-to-Ambient	$R_{\theta JA}$	250	°C/W
Storage Temperature Range	T_{STG}	-55 to 150	°C
Operating Junction Temperature Range	T_J	-55 to 150	°C

Electrical characteristics (Ta=25℃, unless otherwise noted)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Static Characteristics						
Drain-Source Breakdown Voltage	BV_{DSS}	VGS=0V , ID=250μA	20	-	-	V
Drain-Source Leakage Current	I_{DSS}	VDS=16V , VGS=0V	-	-	1	uA
Gate-Source Leakage Current	I_{GSS}	VGS=±10V , VDS=0V	-	-	±100	nA
Gate Threshold Voltage	$V_{GS(th)}$	VDS=VGS , ID=250μA	0.5	0.7	1.0	V
Static Drain-Source On-Resistance	$R_{DS(ON)}$	VGS=4.5V , ID =1.5A	-	45	60	mΩ
		VGS=2.5V , ID =1A	-	60	80	
Dynamic characteristics						
Input Capacitance	C_{iss}	VDS=10V , VGS=0V , f=1MHz	-	277	-	pF
Output Capacitance	C_{oss}		-	65	-	
Reverse Transfer Capacitance	C_{rss}		-	35	-	
Total Gate Charge	Q_g	VDS=10V , VGS=4.5V , ID=2.5A	-	7.0	-	nC
Gate-Source Charge	Q_{gs}		-	1.2	-	
Gate-Drain Charge	Q_{gd}		-	2.6	-	
Gate Plateau Voltage	$V_{plateau}$		-	1.8	-	V
Switching Characteristics						
Turn-On Delay Time	$t_{d(on)}$	VDD=10V VGS=4.5V , RG=6Ω , ID=1A	-	2.65	-	nS
Turn-On Rise Time	t_r		-	4.2	-	
Turn-Off Delay Time	$t_{d(off)}$		-	9.9	-	
Turn-Off Fall Time	t_f		-	5.1	-	
Source-Drain Diode characteristics						
Diode Forward Voltage	V_{SD}	VGS=0V , IS=1A , TJ=25℃	-	-	1.2	V

.

Typical Characteristics



Output Characteristics



Transfer Characteristics



Capacitance Characteristics



Gate Charge



Current dissipation



Power dissipation



RDS(on) VS Drain Current



Forward characteristics of reverse diode



Normalized breakdown voltage



Normalized Threshold voltage



Safe Operation Area



Pulse Width (s)
Normalized Maximum Transient Thermal Impedance

Test Circuit

Gate Charge



Resistive Load Switching Time



Drain-Source Body Diode Reverse Recovery



Temperature Profile for IR Reflow Soldering



Profile Feature	Sn-Pb Eutectic Assembly	Pb-Free Assembly
Preheat & Soak Temperature min (Tsmin) Temperature max (Tsmax) Time (Tsmin to Tsmax) (ts)	 100°C 150°C 60-120 seconds	 150°C 200°C 60-120 seconds
Average ramp-up rate (Tsmax to Tp)	3 °C/second max.	3°C/second max.
Liquidous temperature (TL) Time at liquidous (tL)	183 °C 60-150 seconds	217°C 60-150 seconds
Peak package body Temperature e (Tp)*	See Classification Temp in table 1	See Classification Temp in table 2
Time (tp)** within 5°C of the specified classification temperature (Tc)	20** seconds	30** seconds
Average ramp-down rate (Tp to Tsmax)	6 °C/second max.	6 °C/second max.
Time 25°C to peak temperature	6 minutes max.	8 minutes max.
* Tolerance for peak profile Temperature (Tp) is defined as a supplier minimum and a user maximum. ** Tolerance for time at peak profile temperature (tp) is defined as a supplier minimum and a user maximum		

Table 1. SnPb Eutectic Process – Classification Temperatures (Tc)

Package Thickness	Volume mm^3 <350	Volume mm^3 ≥350
<2.5 mm	235 °C	220 °C
≥2.5 mm	220 °C	220 °C

Table 2. Pb-free Process – Classification Temperatures (Tc)

Package Thickness	Volume mm^3 <350	Volume mm^3 350-2000	Volume mm^3 >2000
<1.6 mm	260 °C	260 °C	260 °C
1.6 mm – 2.5 mm	260 °C	250 °C	245 °C
≥2.5 mm	250 °C	245 °C	245 °C

SOT-23 Tape and Reel

SOT-23 Embossed Carrier Tape



Packaging Description:

SOT-23 parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 3,000 units per 7" or 17.8cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

Dimensions are in millimeter										
Pkg type	A	B	C	d	E	F	P0	P	P1	W
SOT-23	3.15	2.77	1.22	Ø1.50	1.75	3.50	4.00	4.00	2.00	8.00

SOT-23 Tape Leader and Trailer



SOT-23 Reel



Dimensions are in millimeter								
Reel Option	D	D1	D2	G	H	I	W1	W2
7"Dia	Ø178.00	54.40	13.00	R78.00	R25.60	R6.50	9.50	12.30

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
3000 pcs	7 inch	45,000 pcs	210×208×205	180,000 pcs	440×440×230	

SOT-23 Package Information



Symbol	Dimensions In Millimeters	
	Min.	Max.
A	0.90	1.15
A1	0.00	0.10
A2	0.90	1.05
b	0.30	0.50
c	0.08	0.15
D	2.80	3.00
E	1.20	1.40
E1	2.25	2.55
e	0.95 REF.	
e1	1.80	2.00
L	0.55 REF.	
L1	0.30	0.50
θ	0°	8°