Ultra Fast Efficient Rectifiers

1 General Description

1.1 Features

- Glass passivated cavity-free junction
- Ideal for surface mount automotive applications
- Ultrafast recovery time for high efficiency
- Built-in strain relief
- Easy pick and place
- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- Lead (Pb)-free component
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC
- High temperature soldering guaranteed:260℃/10 seconds at terminals

REVERSE VOLTAGE
50-600V
FORWARD CURRENT
2Ampere

1.2 Typical Applications

- Power Supply
- Inverter
- Converter
- Freewheeling diode applications



1.3 Mechanical Data

- Case: JEDEC SMB(DO-214AA) molded plastic body
- Terminals: solder plated ,solderable per MIL-STD-750,method 2026
- Polarity: color band denotes cathode end
- Mounting Position: Any

2 Maximum Ratings(TA=25℃ Unless otherwise specified)

PARAMETER	SYMBOL	ES2AB	ES2BB	ES2DB	ES2FB	ES2GB	ES2JB	UNIT
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	50	100	200	300	400	600	V
Maximum RMS Voltage	V_{RMS}	35	70	140	210	280	420	V
Maximum DC Blocking Voltage	V_{DC}	50	100	200	300	400	600	V
Maximum Average Forward Rectified Current at T_L=110℃	$I_{F(AV)}$	2.0						A
Peak Forward Surge Current 8.3 ms single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	65.0					60.0	A
Operating Temperature Range	T_J	-55 to +150						℃
Storage Temperature Range	T_{STG}	-55 to +150						℃
Typical Thermal Resistance(Note3)	$R_{\theta JA}$	20						℃/W

Notes:
1.Reverse Recovery Test conditions: I_F=0.5A,I_R =1.0A,I_{RR} =0.25A.
2.Measured at 1MH and applied reverse voltage of 4.0 Volts
3.Thermal Resistance From Junction To Ambient P C B Mounted On 0.2x0.2”(5.0x5.0mm) Copper Pad Areas
4.Single phase, half wave, 60Hz resistive or inductive load,for capacitive load, derate by 20%.

3 Electrical Characteristics(TA=25℃ Unless otherwise specified)

PARAMETER		SYMBOL	ES2AB	ES2BB	ES2DB	ES2FB	ES2GB	ES2JB	UNIT
Maximum instantaneous Forward Voltage at 2.0A		V_F	0.95			1.25		1.7	V
Reverse Current at Rated DC Blocking Voltage	Ta =25℃	I_R	5.0						μA
	Ta=125℃		100						
Maximum reverse recovery time(Note1)		t_{rr}	35						ns
Typical junction capacitance(Note2)		C_J	25						pF

4 Characteristics Curves(TA=25℃ Unless otherwise specified)

FIG.1-TYPICAL FORWARD CURRENT DERATING CURVE



FIG.2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT



FIG.3-TYPICAL InsTANTANEOUS FORWARD CHARACTERISTICS



FIG.4-TYPICAL REVERSE CHARACTERISTICS



FIG.5-TYPICAL JUNCTION CAPACITANCE



5 Package Outline Dimensions



Symbol	Millimeters		Inches	
	Min	Max	Min	Max
A	1.91	2.20	0.075	0.086
B	3.30	3.94	0.130	0.155
C	4.06	4.76	0.160	0.187
D	2.13	2.44	0.083	0.096
E	0.76	1.52	0.030	0.060
F	5.08	5.59	0.200	0.220
G	0.152	0.305	0.006	0.012
H	-	0.203	-	0.008

6 Ordering Information

PACKAGE	UNIT WEIGHT (g)	REEL (pcs)	CARTON (pcs)
SMB	Approximate 0.18	3000	48000

Disclaimer

1. All information contained in this document is for reference only. Shandong Baocheng Electronics Co.,Ltd reserves the right to revise this document, product specifications and related data at any time without prior notice. Customers shall obtain and confirm the latest product documents and specifications before purchasing or using the products.

2. Under no circumstances shall the Company be liable for any failure or damage caused by the operation of semiconductor devices beyond the maximum rated values.

3. Shandong Baocheng Electronics Co.,Ltd does not warrant the suitability of its products for any specific application and assumes no responsibility for customer's complete machine design or application debugging. Without written approval, products are prohibited from being used as key components of life support equipment. The Company shall not be liable for any consequences arising from unauthorized use.

4. No intellectual property license of Shandong Baocheng Electronics Co.,Ltd is granted, explicitly or implicitly, through this document.