

ATGBICS CWDM-SFP-1610-80 Cisco Compatible Transceiver CWDM SFP 1000Base (80km, SMF, LC, 1610nm)

Brand : ATGBICS

Product code: CWDM-SFP-1610-80-C

Product name : CWDM-SFP-1610-80 Cisco Compatible Transceiver CWDM SFP 1000Base (80km, SMF, LC, 1610nm)




CWDM-SFP-1610-80 Cisco Compatible Transceiver CWDM SFP 1000Base (80km, SMF, LC, 1610nm)

ATGBICS CWDM-SFP-1610-80 Cisco Compatible Transceiver CWDM SFP 1000Base (80km, SMF, LC, 1610nm):

ATGBICS CWDM-SFP-1610-80 1000Base CWDM supports a distance of up to 80km over single mode fibre (SMF) using a wavelength of 1610nm via an LC connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of CiscoCWDM-SFP-1610-80= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.



Performance		Features	
SFP transceiver type *	Fiber optic	Certification	CE, FCC, RoHS
Maximum data transfer rate *	1250 Mbit/s	Power	
Interface type *	SFP		
Single-mode fiber (SMF) supported	✓	Input voltage	3.3 V
Multi-mode fiber (MMF) supported	✗	Maximum voltage	3.5 V
Fiber optic connector	LC	Power consumption (typical)	1 W
SFP transceiver standard	CWDM	Operational conditions	
Maximum transfer distance	80000 m	Maximum operating temperature	70 °C
Wavelength	1610 nm	Operating temperature (T-T)	0 - 70 °C
Coarse Wavelength Division Multiplexing (CWDM)	✓	Storage temperature (T-T)	-40 - 85 °C
Ethernet LAN	✓	Operating relative humidity (H-H)	0 - 95%
Ethernet interface type	Gigabit Ethernet	Storage relative humidity (H-H)	0 - 95%
Digital Diagnostics Monitoring (DDM)	✓	Weight & dimensions	
Features		Width	13.4 mm
Product colour	Silver	Depth	56.5 mm
Housing material	Metal	Height	8.5 mm
Plug and Play	✓	Weight	15 g
Hot-swap	✓	Packaging data	
Easy to install	✓	Number of products included	1 pc(s)
Country of origin	United Kingdom	Package type	Box
Brand compatibility	Cisco	Technical details	
		Sustainability compliance	✓
		Sustainability certificates	RoHS
		Doesn't contain	Lead



5056468714336

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.