## ATGBICS ONS-SE-100-BX10U Cisco Compatible Transceiver SFP 100Base-BX-U (Tx1310nm/Rx1550nm, 10km, SMF, DOM)

Brand: ATGBICS Product code: ONS-SE-100-BX10U-C

**Product name :** ONS-SE-100-BX10U Cisco Compatible Transceiver SFP 100Base-BX-U (Tx1310nm/Rx1550nm,

10km, SMF, DOM)

ATGBICS ATPO18-35SL10D
RC (C Most Attraction of the COMPANY ATTRACTOR O

 ${\tt ONS-SE-100-BX10U~Cisco~Compatible~Transceiver~SFP~100Base-BX-U~(Tx1310nm/Rx1550nm,~10km,~SMF,~DOM)}$ 

 $ATGBICS\ ONS-SE-100-BX10U\ Cisco\ Compatible\ Transceiver\ SFP\ 100Base-BX-U\ (Tx1310nm/Rx1550nm,\ 10km,\ SMF,\ DOM):$ 

ATGBICS ONS-SE-100-BX10U 100Base-BX SFP supports a distance of up to 10km over single mode fibre (SMF) using a wavelength of Tx1310nm/Rx1550nm via an LC connector. This bidirectional unit must be used with another transceiver or network appliance of complimenting wavelengths. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of CiscoONS-SE-100-BX10U= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.



Performance		Power	
SFP transceiver type * Fiber optic  Maximum data transfer rate * 100 Mbit/s  Interface type * SFP  Single-mode fiber (SMF) supported  Multi-mode fiber (MMF) supported  Fiber optic connector  LC  SFP transceiver standard  Maximum transfer distance  Tx wavelength (max)  Fiber optic  10000 m  1310 nm	100 Mbit/s	Input voltage Maximum voltage Power consumption (typical)	3.3 V 3.5 V 1 W
	X LC BX-U 10000 m	Operational conditions  Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	70 °C 0 - 70 °C -40 - 85 °C 0 - 95% 0 - 95%
Rx wavelength (max) Ethernet LAN Ethernet interface type Digital Diagnostics Monitoring (DDM)	1550 nm  ✓ Fast Ethernet ✓	Weight & dimensions Width Depth Height	12.7 mm 55.9 mm 7.62 mm
Features  Product colour  Housing material  Plug and Play  Hot-swap	Silver Metal ✓	Packaging data  Number of products included  Package type	19 g 1 pc(s) Box
Easy to install  Country of origin  Brand compatibility  Cisco  Certification  CE, FCC, RoHS	Technical details Sustainability compliance Sustainability certificates Doesn't contain	✓ RoHS Lead	



5056468717573

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.