# 3-647609-5 ACTIVE

#### MTA 100

TE Internal #: 3-647609-5

PCB Mount Header, Vertical, Wire-to-Board, 5 Position, 2.54 mm [.1


in] Centerline, Partially Shrouded, Tin, Through Hole - Solder,

Signal, MTA 100


View on TE.com >



Connectors > PCB Connectors > PCB Headers & Receptacles > PCB Header: Polyester, Vertical, Unshrouded, No Mating Alignment











Connector System: Wire-to-Board

Number of Positions: 5
Number of Rows: 1

Centerline (Pitch): 2.54 mm [ .1 in ]
PCB Mount Orientation: Vertical

All PCB Header: Polyester, Vertical, Unshrouded, No Mating Alignment (134)

#### **Features**

### **Product Type Features**

| Connector System                  | Wire-to-Board         |
|-----------------------------------|-----------------------|
| Header Type                       | Partially Shrouded    |
| Sealable                          | No                    |
| Connector & Contact Terminates To | Printed Circuit Board |
| PCB Connector Assembly Type       | PCB Mount Header      |
| Configuration Features            |                       |
| Number of Positions               | 5                     |
| Number of Rows                    | 1                     |
| PCB Mount Orientation             | Vertical              |
| Electrical Characteristics        |                       |
| Operating Voltage                 | 250 VAC               |



| Primary Product Color                                   | Black                        |
|---|------------------------------|
| Contact Features  |                              |
| Contact Mating Area Length                              | 7.37 mm[.29 in]              |
| Mating Square Post Dimension                            | .64 mm[.025 in]              |
| PCB Contact Termination Area Plating Material Thickness | 3.81 – 6.3 μm[150 – 250 μin] |
| Contact Layout  | Inline                       |
| Contact Underplating Material Thickness                 | 1.27 μm[50 μin]              |
| Contact Mating Area Plating Material Thickness          | 3.81 – 6.3 μm[150 – 250 μin] |
| PCB Contact Termination Area Plating Material Finish    | Matte                        |
| Contact Shape & Form                                    | Square                       |
| Contact Mating Area Plating Material Finish             | Matte                        |
| Contact Underplating Material                           | Nickel                       |
| PCB Contact Termination Area Plating Material           | Tin                          |
| Contact Base Material                                   | Copper Alloy                 |
| Contact Mating Area Plating Material                    | Tin                          |
| Contact Type  | Pin                          |
| Contact Current Rating (Max)                            | 5 A                          |
| ermination Features                                     |                              |
| Square Termination Post & Tail Dimension                | .64 mm[.025 in]              |
| Termination Post & Tail Length                          | 3.43 mm[.135 in]             |
| Termination Method to Printed Circuit Board             | Through Hole - Solder        |
| Mechanical Attachment                                   |                              |
| PCB Mount Alignment Type                                | Peg                          |
| Mating Alignment Type                                   | Polarization                 |
| Mating Retention  | With                         |
| Panel Mount Feature                                     | Without                      |
| PCB Mount Retention Type                                | Tab                          |
| Mating Retention Type                                   | Friction Lock                |
| Connector Mounting Type                                 | Board Mount                  |
| Mating Alignment  | With                         |
| PCB Mount Alignment                                     | With                         |
| PCB Mount Retention                                     | With                         |

### **Housing Features**



| Housing Material            | Polyester - GF             |
|-----------------------------|----------------------------|
| Centerline (Pitch)          | 2.54 mm[.1 in]             |
| Dimensions                  |                            |
| Connector Height            | 8.81 mm[.34 in]            |
| PCB Thickness (Recommended) | 1.57 mm[.062 in]           |
| Usage Conditions            |                            |
| Operating Temperature Range | -55 – 105 °C[-67 – 221 °F] |
| Operation/Application       |                            |
| Circuit Application         | Signal                     |
| Industry Standards          |                            |
| Agency/Standard             | CSA, UL                    |
| Approved Standards          | CSA LR7189, UL E28476      |
| UL Flammability Rating      | UL 94V-0                   |
| Packaging Features          |                            |
| Packaging Quantity          | 500                        |

## **Product Compliance**

Packaging Type

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU                  | Compliant   |
|---|---|
| EU ELV Directive 2000/53/EC                   | Compliant   |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold   |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC |
| Halogen Content                               | Not Low Halogen - contains Br or Cl > 900 ppm.  |
| Solder Process Capability                     | Wave solder capable to 240°C  |

Bag, Box

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these



limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts







## Also in the Series MTA 100



Insertion & Extraction Tools(2)



PCB Connector Covers(69)



PCB Connector Keying(1)




PCB Headers & Receptacles(440)



Standard Rectangular Connectors(495)



Wire-to-Board Connector Assemblies & Housings(1)




# **Customers Also Bought**

PCB Mount Header, Vertical, Wire-to-Board, 5 Position, 2.54 mm [.1 in] Centerline, Partially Shrouded, Tin, Through Hole - Solder, Signal, MTA 100
























#### **Documents**

**Product Drawings** 

05P MTA100 HDR ASSY F/L LF

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_3-647609-5\_D.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_3-647609-5\_D.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_3-647609-5\_D.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

**Product Specifications** 

PCB Mount Header, Vertical, Wire-to-Board, 5 Position, 2.54 mm [.1 in] Centerline, Partially Shrouded, Tin, Through Hole - Solder, Signal, MTA 100



**Product Specification** 

English

Product Environmental Compliance

TE Material Declaration

English

Agency Approvals

Agency Approval Document

English