

1586861-4

✓ ACTIVE

VAL-U-LOK

TE Internal #: 1586861-4

Rectangular Power Connectors, Housing, Plug, Wire-to-Panel /
 Wire-to-Wire, 4 Position, 4.2 mm [.165 in] Centerline, Wire & Cable,
 UL 94V-2

[View on TE.com >](#)

Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors



Rectangular Power Connector Type: **Housing**

Connector & Housing Type: **Plug**

Connector System: **Wire-to-Panel, Wire-to-Wire**

Number of Positions: **4**

Centerline (Pitch): **4.2 mm [.165 in]**

Features

Product Type Features

Rectangular Power Connector Type	Housing
Connector & Housing Type	Plug
Connector System	Wire-to-Panel, Wire-to-Wire
Sealable	No
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Number of Positions	4
Number of Power Positions	0
Number of Signal Positions	0
Number of Rows	2

Electrical Characteristics

Operating Voltage	600 VAC
-------------------	---------

Contact Features

Contact Layout	Matrix, Square Grid
Contact Retention Within Housing	Without
Contact Type	Pin

Termination Features

Termination Method to Wire & Cable	Crimp
------------------------------------	-------

Mechanical Attachment

Connector Mounting Type	Panel Mount
-------------------------	-------------

Housing Features

Centerline (Pitch)	4.2 mm [.165 in]
Housing Color	White
Housing Material	Polyamide

Dimensions

Connector Height	9.6 mm [.378 in]
Product Width	23.9 mm [.94 in]
Product Length	9.6 mm [.378 in]
Compatible Insulation Diameter Range	1.2 – 3.1 mm [.047 – .122 in]
Row-to-Row Spacing	4.2 mm [.165 in]

Usage Conditions

Operating Temperature Range	-40 – 105 °C [-40 – 221 °F]
-----------------------------	-----------------------------

Operation/Application

Circuit Application	Power & Signal
---------------------	----------------

Identification Marking

Circuit Identification Feature	With
--------------------------------	------

Industry Standards

CSA Rating	208567
UL Rating	Recognized
Agency/Standard	CSA, UL
Approved Standards	UL E28476
UL Flammability Rating	UL 94V-2
Glow Wire Rating	GWT 750°C (Without Flame)

Packaging Features

Packaging Quantity	1
Packaging Method	Package

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2021 (211) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

			
TE Part # 2029265-4 4P VAL-U-LOK VRTHDR W/PGS GW	TE Part # 1586765-4 4P RCPT VAL-U-LOK GW	TE Part # 2296205-4 4P RCPT VAL-U-LOK GWT/V0	TE Part # 1586768-4 4P VERT HDR VAL-U-LOK GW



TE Part # 1586861-4
4P VAL-U-LOK R/A HDR GW

TE Part # 2029059-4
4P VAL-U-LOK VRTHDR W/PGS GW


Customers Also Bought



TE Part #282080-3
AMP SUPERSEAL 1.5 SERIES 2P PL



TE Part #1586862-4
4P FH PLUG VAL-U-LOK FH GW



TE Part #1586765-4
4P RCPT VAL-U-LOK GW



TE Part #42563-8
250 FASTON FLAG REC 12-10 AWG
TPBZ



TE Part #42563-2
250 FASTON FLAG REC 12-10 AWG
TPBR



TE Part #282403-1
MINI MIC SRS REC CONT



TE Part #1416010-1
V23132A2001B200



TE Part #1393315-2
V23132A2001A200=HCR



TE Part #5-1377175-4
SMP 0-0165035-0

Documents

Product Drawings

[4P PM PLUG VAL-U-LOK PM GW](#)

English

CAD Files

[Customer View Model](#)

[ENG_CVM_CVM_1586861-4_B.2d_dxf.zip](#)

English

[3D PDF](#)

3D

Customer View Model[ENG_CVM_CVM_1586861-4_B.3d_jgs.zip](#)

English

Customer View Model[ENG_CVM_CVM_1586861-4_B.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.**Datasheets & Catalog Pages**[VAL-U-LOK_GLOW_WIRE_CONNECTORS](#)

English

Product Specifications[Application Specification](#)

English

Agency Approvals[UL Report](#)

English