

AMP

TE Internal #: 5-228618-1


RF Contacts, Cable-to-Cable, 1 Position, Wire & Cable, Pin, Straight, RG 188 / RG 174 / RG 316, Gold, 1 A, Power & Signal,

Cable Mount (Free-Hanging)

View on TE.com >



Connectors > RF Connectors > RF Contacts



Connector System: Cable-to-Cable

Number of Positions: 1

Connector & Contact Terminates To: Wire & Cable

Contact Type: Pin

Contact Orientation: Straight

Features

Product Type Features

Connector System	Cable-to-Cable
Connector & Contact Terminates To	Wire & Cable
Compatible With RF Cable Type	RG 174, RG 188, RG 316
Configuration Features	
Number of Positions	1
Electrical Characteristics	
Impedance Options	Non-Matched
Body Features	
Outer Shell Material	Brass
Outer Shell Plating Material	Gold
Outer Shell Plating Thickness	30 μin
Contact Features	

	30 μin
RF Connector Center Contact Material	Beryllium Copper
Contact Type	Pin
Contact Orientation	Straight
RF Connector Center Contact Plating Material	Gold
Contact Mating Retention	Without



Contact Current Rating (Max)	1 A
Mechanical Attachment	
Connector Mounting Type	Cable Mount (Free-Hanging)
Usage Conditions	
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]
Operation/Application	
Circuit Application	Power & Signal
Packaging Features	
Packaging Method	Carton
Other	
RF Connector Comment	Non-Impedance Matched and 50 Ohm are not intermatable.
Dielectric Material	PTFE

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Pb (4% in Contact/Component) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Bromine/Chlorine - Br and Cl < 900 ppm per homogenous material. Also BFR /CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part



numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Customers Also Bought



















Documents

Product Drawings

PIN, STRAIGHT, SIZE 8, AMPLIMITE

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_5-228618-1_M.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_5-228618-1_M.3d_igs.zip

RF Contacts, Cable-to-Cable, 1 Position, Wire & Cable, Pin, Straight, RG 188 / RG 174 / RG 316, Gold, 1 A, Power & Signal, Cable Mount (Free-Hanging)



English

Customer View Model
ENG_CVM_CVM_5-228618-1_M.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.