

APPLICABLE STANDARD		SPECIFICATIONS			
RATING	OPERATING TEMPERATURE RANGE	-55 °C TO 85 °C	STORAGE TEMPERATURE RANGE	-10°C TO 60 °C ⁽¹⁾	
	VOLTAGE	50 V AC	OPERATING HUMIDITY RANGE	RELATIVE HUMIDITY 95 % RH MAX. ⁽²⁾	
	CURRENT	0.3 A	STORAGE HUMIDITY RANGE	40 % TO 70 % ⁽¹⁾	
CONSTRUCTION					
GENERAL EXAMINATION	VISUAL AND WITH MEASURING INSTRUMENT.		ACCORDING TO DRAWING.		<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
MARKING	CONFIRM VISUALLY.				<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
ELECTRIC CHARACTERISTICS					
CONTACT RESISTANCE [EIA-364-23]	100 mA and 20 mv OPEN CIRCUIT MAX.			8mm height : 80 mΩ MAX. 9mm height : 85 mΩ MAX. 10mm height : 90 mΩ MAX.	<input checked="" type="checkbox"/> <input type="checkbox"/>
INSULATION RESISTANCE [EIA-364-21]	100 V DC.			100 MΩ MIN.	<input checked="" type="checkbox"/> <input type="checkbox"/>
VOLTAGE PROOF [EIA-364-20]	150 V AC FOR 1 MINUTE.			NO FLASHOVER OR BREAKDOWN.	<input checked="" type="checkbox"/> <input type="checkbox"/>
MECHANICAL CHARACTERISTICS					
INSERTION AND WITHDRAWAL FORCES [EIA-364-13]	MEASURED BY APPLICABLE CONNECTORS.			INSERTION FORCE: 72 N MAX. WITHDRAWAL FORCE: 3 N MIN.	<input checked="" type="checkbox"/> <input type="checkbox"/>
MECHANICAL OPERATION [EIA-364-09]	50 TIMES INSERTIONS AND EXTRACTION.			① CONTACT RESISTANCE CHANGE: 20 mΩ OR LESS ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	<input checked="" type="checkbox"/> <input type="checkbox"/>
RANDOM VIBRATION [EIA-364-28]	FREQUENCY: 20 TO 500 Hz POWER SPECTRAL DENSITY: 0.02 G ² /Hz OVERALL rms G: 3.1 Grms FOR 15 MINUTES IN THREE DIRECTIONS.			1) NO ELECTRICAL DISCONTINUITY OF 1μs OR MORE. 2) NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	<input checked="" type="checkbox"/> <input type="checkbox"/>
SHOCK [EIA-364-27]	490 m/s ² , DURATION OF PULSE: 11 ms 3 EACH DIRECTION, 3 AXIS.				<input checked="" type="checkbox"/> <input type="checkbox"/>
ENVIRONMENTAL CHARACTERISTICS					
THERMAL SHOCK [EIA-364-32]	TEMPERATURE: -55 → 15 ~ 35 → 85 → 15 ~ 35 °C TIME: 30 → 5 → 30 → 5 min. UNDER 10 CYCLES			1) CONTACT RESISTANCE CHANGE: 20 mΩ OR LESS 2) NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	<input checked="" type="checkbox"/> <input type="checkbox"/>
CYCLIC TEMPERATURE AND HUMIDITY [EIA-364-31]	@ 25 °C, 80% RH: 60 MIN DWELL TIME 30 MIN RAMP TIME @ 65 °C, 50% RH: 60 MIN DWELL TIME UNDER 24 CYCLES.				<input checked="" type="checkbox"/> <input type="checkbox"/>
DRY HEAT [EIA-364-17]	EXPOSED AT 105 °C, 1000 hr.				<input checked="" type="checkbox"/> <input type="checkbox"/>
MIXED FLOWING GAS [EIA-364-65]	EXPOSED AT 30 °C, 70% Cl ₂ : 10 ppb, NO ₂ : 200 ppb, H ₂ S : 10 ppb, SO ₂ : 100 ppb UNMATED 7 DAYS, MATED 7 DAYS.			1) CONTACT RESISTANCE CHANGE: 20 mΩ OR LESS 2) NO HEAVY CORROSION.	<input checked="" type="checkbox"/> <input type="checkbox"/>
REMARK ⁽¹⁾ THIS STORAGE INDICATES A LONG-TERM STORAGE STATE FOR THE UNUSED PRODUCT BEFORE THE BOARD MOUNTED. ⁽²⁾ NO DEW CONDENSATION IS PERMITTED.				APPROVED	TM. MATSUO 17.07.20
				CHECKED	MK. EZAKI 17.07.20
				DESIGNED	AS. MATSUZAWA 17.07.20
				DRAWN	AS. MATSUZAWA 17.07.20
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC-361677-03-00
	SPECIFICATION SHEET		PART NO.	FX10-120IP-8H(03)	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL608-0017-3-03	 1/1